

Cisco UCS C220 M3 High-Density Rack Server Large Form Factor Hard Disk Drive - rack-mountable - no CPU - 0 GB - no HDD



24-08-2024

SKU	UCSC-C220-M3L=
Product Description:	Cisco UCS C220 M3 High-Density Rack Server Large Form Factor Hard Disk Drive - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA2011 Socket
RAM:	0 GB DDR3 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	2-way
Hot-Swap Bays Qty:	4

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 90% (non-condensing)

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA2011 Socket
Chipset Type:	Intel C600

Dimensions & Weight

Width:	43 cm
Depth:	72.4 cm
Height:	4.3 cm
Weight:	10 kg

RAM

Installed Size:	0 GB
Technology:	DDR3 SDRAM - ECC
Features:	Registered, Memory Mirroring, low-voltage

Manufacturer Warranty

Service & Support:	Limited warranty - advance parts replacement - 3 years - response time: next business day
--------------------	---

Power

Device Type:	Power supply
--------------	--------------

Hard Drive

Hard Drive

Type: No HDD

Storage Controller

Type: RAID - integrated

Controller Interface Type: SATA 3Gb/s

Channel Qty: 4

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Type: Integrated

Graphics Processor: Matrox G200e

Video Memory: 256 MB

Video Interfaces: VGA

Networking

Ethernet Ports: 2 x Gigabit Ethernet

Ethernet Controller: Intel I350

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Remote Management Protocol: IPMI 2.0, CLI

Power

Installed Qty: 0

Max Supported Qty: 2

Voltage Required: AC 120/230 V (50/60 Hz)

Miscellaneous

Included Accessories: Rack rail kit

Compliant Standards: CISPR 22 Class A, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, VCCI Class A ITE, EN 61000-3-3, EN55024, EN55022 Class A, AS/NZS 60950-1, ICES-003 Class A, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1, GB 4943, EN 300 386

Expansion / Connectivity

Bays: 8 (total) / 8 (free) x hot-swap 3.5"

Slots: 2 (total) / 2 (free) x CPU ; 16 (total) / 16 (free) x memory ; 1 (total) / 1 (free) x PCIe 2.0 x8 ; 1 (total) / 1 (free) x PCIe 2.0 x16

Interfaces: 1 x serial ; 2 x USB 2.0 ; 1 x management ; 1 x VGA ; 2 x LAN (Gigabit Ethernet) ; 1 x KVM

