

Cisco UCS C220 M4 High-Density Rack Server (Large Form Factor Disk Drive Model) - rack-mountable - no CPU - 0 GB - no HDD



Not in stock

SKU	UCSC-C220-M4L-CH
Product Description:	Cisco UCS C220 M4 High-Density Rack Server (Large Form Factor Disk Drive Model) - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA2011-v3 Socket
RAM:	0 GB (installed) / 384 GB (max) - DDR4 SDRAM

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	2-way
Hot-Swap Bays Qty:	4

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA2011-v3 Socket
Chipset Type:	Intel C612

RAM

Installed Size:	0 GB / 384 GB (max)
Technology:	DDR4 SDRAM
Form Factor:	DIMM 288-pin
Slots:	24 (Total) / 24 (empty)

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	10 - 90% (non-condensing)

Dimensions & Weight

Width:	43 cm
Depth:	75.6 cm
Height:	4.32 cm

Manufacturer Warranty

Service & Support:	Limited warranty - replacement - 3 years - response time: next business day
--------------------	---

Operating System / Software

OS Provided:	No operating system
--------------	---------------------

Power

RAM

RAM Supported: 384 GB registered - ECC ; 768 GB Load-Reduced - ECC

Hard Drive

Type: No HDD

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Type: Integrated

Graphics Processor: Matrox G200e

Video Memory: 8 MB

Video Interfaces: VGA

Networking

Ethernet Ports: 2 x Gigabit Ethernet

Ethernet Controller: Intel I350

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Power

Device Type: Power supply - hot-plug

Power Redundancy: Optional

Installed Qty: 0

Max Supported Qty: 2

Miscellaneous

Compliant Standards: CISPR 22 Class A, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, EN 61000-3-3, EN55024, EN55022 Class A, AS/NZS 60950-1, ICES-003 Class A, UL 60950-1 Second Edition, Directive 2004/108/EC, CSA C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, Directive 2006/95/EC, VCCI Class A, KN24, KN22 Class A, GB4943.1-2001, EN 300 386, EN 300386

Pricing Type: DISTI

Expansion / Connectivity

Bays: 4 (total) / 4 (free) x hot-swap 3.5" LFF

Slots: 2 (total) / 2 (free) x CPU ; 24 (total) / 24 (free) x DIMM 288-pin ; 1 (total) / 1 (free) x PCIe 3.0 x24 - three-quarter-length, full-height (x16 mode) ; 1 (total) / 1 (free) x PCIe 3.0 x24 - half-length, low-profile (x16 mode) ; 2 (total) / 2 (free) x SD card (internal)

Interfaces: 2 x USB 3.0 (2 rear) ; 1 x VGA (1 rear) ; 1 x serial - RJ-45 (1 rear) ; 2 x LAN (Gigabit Ethernet) - RJ-45 (2 rear) ; 1 x management (NIC) - RJ-45 (1 rear) ; 1 x KVM (1 in front)

