

Cisco UCS C240 M3 High-Density Rack-Mount Server Small Form Factor - rack-mountable - no CPU - 0 GB - no HDD



Not in stock

SKU	UCSC-C240-M3S2-CH2
Product Description:	Cisco UCS C240 M3 High-Density Rack-Mount Server Small Form Factor - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	2U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA2011 Socket
RAM:	0 GB (installed) / 384 GB (max) - DDR3 SDRAM - Advanced ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 2U
Server Scalability:	2-way
Hot-Swap Bays Qty:	16

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 90% (non-condensing)

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA2011 Socket
Chipset Type:	Intel C600

Dimensions & Weight

Width:	44.55 cm
Depth:	71.23 cm
Height:	8.7 cm
Weight:	14.6 kg

RAM

Installed Size:	0 GB / 384 GB (max)
Technology:	DDR3 SDRAM - Advanced ECC
Form Factor:	DIMM 240-pin
Slots:	24 (Total) / 24 (empty)
Features:	Registered, Memory Mirroring, low-voltage

Manufacturer Warranty

Service & Support:	Limited warranty - replacement - 3 years - response time: next business day
--------------------	---

Power

Device Type:	Power supply
Power Redundancy:	Optional
Installed Qty:	0

Hard Drive

Type: No HDD

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Type: Integrated

Graphics Processor: Matrox G200e

Video Memory: 256 MB

Video Interfaces: VGA

Networking

Ethernet Ports: 4 x Gigabit Ethernet

Ethernet Controller: Intel I350

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Remote Management Protocol: IPMI 2.0, CLI

Power

Max Supported Qty: 2

Voltage Required: AC 120/230 V (50/60 Hz)

Miscellaneous

Included Accessories: Rack rail kit

Compliant Standards: CISPR 22 Class A, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, VCCI Class A ITE, EN 61000-3-3, EN55024, EN55022 Class A, AS/NZS 60950-1, ICES-003 Class A, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1, GB 4943, EN 300 386

Pricing Type: DISTI

Expansion / Connectivity

Bays: 16 (total) / 16 (free) x hot-swap 2.5"

Slots: 2 (total) / 2 (free) x CPU ; 24 (total) / 24 (free) x DIMM 240-pin ; 2 (total) / 2 (free) x PCIe 3.0 x24 - three-quarter-length, full-height (x16 mode) ; 1 (total) / 1 (free) x PCIe 3.0 x16 - half-length, low-profile (x8 mode) ; 1 (total) / 1 (free) x PCIe 3.0 x16 - three-quarter-length, full-height (x8 mode) ; 1 (total) / 1 (free) x PCIe 3.0 x16 - half-length, full-height (x8 mode)

Interfaces: 1 x serial ; 2 x USB 2.0 ; 1 x management (NIC) ; 1 x VGA ; 8 x LAN (Gigabit Ethernet) ; 1 x KVM

