

Cisco Unified IP Phone Power Injector - PoE injector - 15.5 Watt



Not in stock

SKU	CP-PWR-INJ=
Product Description:	Cisco Unified IP Phone Power Injector - PoE injector - 15.5 Watt
Device Type:	PoE injector - external
Weight:	300 g
Output Voltage:	-48 V
Power Capacity:	15.5 Watt
Dimensions (WxDxH):	11.8 cm x 13.8 cm x 4.1 cm
Designed For:	IP Phone 7902G, 7905, 7905G, 7906G, 7910, 7910+SW, 7910G, 7910G+SW, 7911G, 7914, 7920, 7935, 7940, 7940G, 7941G-GE, 7960, 7960G, 7961G, 7961G-GE, 7970G, 7971G-GE, 7985G, 7985G NTSC, 7985G PAL; Unified IP Phone 7912G, 7941G



General

Device Type: PoE injector - external

Power Device

Input Voltage Range: AC 90 - 264 V

Frequency Required: 47 - 63 Hz

Output Voltage: -48 V

Power Capacity: 15.5 Watt

Expansion / Connectivity

Interfaces: 2 x Gigabit LAN - RJ-45

Compatibility Information

Designed For: Cisco IP Phone 7902G, 7905, 7905G, 7906G, 7910, 7910+SW, 7910G, 7910G+SW, 7911G, 7914, 7920, 7935, 7940, 7940G, 7941G-GE, 7960, 7960G, 7961G, 7961G-GE, 7970G, 7971G-GE, 7985G, 7985G NTSC, 7985G PAL ; Cisco Unified IP Phone 7912G, 7941G

Dimensions & Weight

Width: 11.8 cm

Depth: 13.8 cm

Height: 4.1 cm

Weight: 300 g

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 10 - 95%

Miscellaneous

Compliant Standards: FCC Class B certified, VCCI Class B ITE, CISPR 22 Class B, CISPR 24, EN 60950, EN 61000-3-2, IEC 60950, EN 61000-3-3, EN55024, UL 60950, EN50082-1, CSA 22.2 No. 60950, EN55022 Class B, ICES-003 Class B, EN 61000-6-1, FCC CFR47 Part 15

