

# Cisco Webex Room USB - video conferencing kit



Not in stock

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| SKU                         | CS-ROOM-USB-K9=                                                 |
| Product Description:        | Cisco Webex Room USB - video conferencing kit                   |
| Device Type:                | Video conferencing kit                                          |
| VoIP Protocols:             | H.323                                                           |
| Codec:                      | H.264, H.265, H.239, G.711, G.722, G.729, G.722.1, AAC-LD, Opus |
| Digital Signaling Protocol: | SIP, H.245, H.460.18, H.460.19, BFCP                            |
| Data Compression Protocol:  | G.711, G.722, H.263, H.264, G.722.1                             |
| Video Input:                | Digital video camera - HDMI                                     |

## General

|                     |                                                                     |
|---------------------|---------------------------------------------------------------------|
| Device Type:        | Video conferencing kit                                              |
| VoIP Protocols:     | H.323                                                               |
| Voice Codecs:       | G.711, G.722, G.729, G.722.1, AAC-LD, Opus                          |
| Video Codecs:       | H.264, H.265, H.239                                                 |
| Quality of Service: | IEEE 802.1Q (VLAN), Differentiated Services (DiffServ), IEEE 802.1p |
| Network Protocols:  | HTTP, DNS, HTTPS, NTP                                               |

Dimensions & Weight Details: Main system - Width 50 cm Depth 7.7 cm Height 8.1 cm Weight 1.5 kg

## Modem

|                             |                                      |
|-----------------------------|--------------------------------------|
| Digital Signaling Protocol: | SIP, H.245, H.460.18, H.460.19, BFCP |
| Data Compression Protocol:  | G.711, G.722, H.263, H.264, G.722.1  |

## Video Input

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Type:                             | Digital video camera (colour) - integrated |
| Interface Type:                   | HDMI                                       |
| Digital Video Capture Resolution: | 3840 x 2160                                |

## Environmental Parameters

|                            |          |
|----------------------------|----------|
| Min Operating Temperature: | 0 °C     |
| Max Operating Temperature: | 35 °C    |
| Humidity Range Operating:  | 10 - 90% |

## Manufacturer Warranty

|                    |                            |
|--------------------|----------------------------|
| Service & Support: | Limited warranty - 90 days |
|--------------------|----------------------------|

## Dimensions & Weight (Shipping)

|                  |         |
|------------------|---------|
| Shipping Width:  | 60.5 cm |
| Shipping Depth:  | 21.6 cm |
| Shipping Height: | 32.6 cm |
| Shipping Weight: | 3.2 kg  |

## Power

|                   |                         |
|-------------------|-------------------------|
| Power Device:     | Power supply            |
| Voltage Required: | AC 120/230 V (50/60 Hz) |

## Miscellaneous

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| Cables Included:      | USB-C to USB-A cable ; Network cable ; HDMI cable |
| Mounting Kit:         | Included                                          |
| Included Accessories: | Remote control, wall mount, privacy cover         |

## Video Input

Video Modes: 4K/1080p

Digital Zoom: 2

Features: Face detection, automatic brightness adjustment, auto white balance, Auto Focus, 120° field of view

## Video Output

Type: Codec board - external

Supported Display Graphics: HDTV (1920x1080), UHD (3840 x 2160)

Digital Video Standard: High-Definition Multimedia Interface (HDMI)

## Audio Input

Type: Microphones - integrated

## Audio Output

Type: Speaker(s)

Audio Amplifier: Integrated

Output Power / Channel: 24 Watt

Frequency Response: 100 - 20000 Hz

## Miscellaneous

Compliant Standards: EMC, AES, RoHS, WEEE

## Expansion / Connectivity

Interfaces: 1 x audio / video - HDMI input - 19 pin HDMI Type A ; 2 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 ; 1 x USB 2.0 ; 1 x USB-C - USB 2.0

## Networking

Connectivity Technology: Wireless, wired

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, IEEE 802.11ac

Network / Transport Protocol: NTP, DHCP, DNS, HTTP, HTTPS

Features: DiffServ support, IPv6 support, Quality of Service (QoS), SSH support, IPv4 support, Class of Service (CoS), automatic gain control (AGC), 802.1x authentication, URI Dialing, CEC 2.0 support

Compliant Standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x

