

Cisco Webex Room USB - video conferencing kit



Not in stock

SKU	CS-ROOM-USB-K9
Product Description:	Cisco Webex Room USB - video conferencing kit
Device Type:	Video conferencing kit
VoIP Protocols:	H.323
Codec:	H.264, H.265, H.239, G.711, G.722, G.729, G.722.1, AAC-LD, Opus
Digital Signaling Protocol:	SIP, H.245, H.460.18, H.460.19, BFCP
Data Compression Protocol:	G.711, G.722, H.263, H.264, G.722.1
Video Input:	Digital video camera - HDMI

General

Device Type:	Video conferencing kit
VoIP Protocols:	H.323
Voice Codecs:	G.711, G.722, G.729, G.722.1, AAC-LD, Opus
Video Codecs:	H.264, H.265, H.239
Quality of Service:	IEEE 802.1Q (VLAN), Differentiated Services (DiffServ), IEEE 802.1p
Network Protocols:	HTTP, DNS, HTTPS, NTP

Dimensions & Weight Details: Main system - Width 50 cm Depth 7.7 cm Height 8.1 cm Weight 1.5 kg

Modem

Digital Signaling Protocol:	SIP, H.245, H.460.18, H.460.19, BFCP
Data Compression Protocol:	G.711, G.722, H.263, H.264, G.722.1

Video Input

Type:	Digital video camera (colour) - integrated
Interface Type:	HDMI
Digital Video Capture Resolution:	3840 x 2160

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	10 - 90%

Manufacturer Warranty

Service & Support:	Limited warranty - 90 days
--------------------	----------------------------

Dimensions & Weight (Shipping)

Shipping Width:	60.5 cm
Shipping Depth:	21.6 cm
Shipping Height:	32.6 cm
Shipping Weight:	3.2 kg

Power

Power Device:	Power supply
Voltage Required:	AC 120/230 V (50/60 Hz)

Miscellaneous

Cables Included:	USB-C to USB-A cable ; Network cable ; HDMI cable
Mounting Kit:	Included
Included Accessories:	Remote control, wall mount, privacy cover

Video Input

Video Modes: 4K/1080p

Digital Zoom: 2

Features: Face detection, automatic brightness adjustment, auto white balance, Auto Focus, 120° field of view

Video Output

Type: Codec board - external

Supported Display Graphics: HDTV (1920x1080), UHD (3840 x 2160)

Digital Video Standard: High-Definition Multimedia Interface (HDMI)

Audio Input

Type: Microphones - integrated

Audio Output

Type: Speaker(s)

Audio Amplifier: Integrated

Output Power / Channel: 24 Watt

Frequency Response: 100 - 20000 Hz

Miscellaneous

Compliant Standards: EMC, AES, RoHS, WEEE

Expansion / Connectivity

Interfaces: 1 x audio / video - HDMI input - 19 pin HDMI Type A ; 2 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 ; 1 x USB 2.0 ; 1 x USB-C - USB 2.0

Networking

Connectivity Technology: Wireless, wired

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, IEEE 802.11ac

Network / Transport Protocol: NTP, DHCP, DNS, HTTP, HTTPS

Features: DiffServ support, IPv6 support, Quality of Service (QoS), SSH support, IPv4 support, Class of Service (CoS), automatic gain control (AGC), 802.1x authentication, URI Dialing, CEC 2.0 support

Compliant Standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x

