

Citizen CT-S2000 - receipt printer - two-colour (monochrome) - thermal line



Not in stock

SKU	CTS2000USBWH
Product Description:	Citizen CT-S2000 - receipt printer - two-colour (monochrome) - thermal line
Printer Type:	Receipt printer - thermal line - two-colour (monochrome)
Weight:	2 kg
Max Media Size:	Roll (8.25 cm)
Min Media Size (Custom):	58 mm
Max Media Size (Custom):	82.5 mm
Print Speed:	Up to 220 mm/sec - max speed

General

Printer Type:	Receipt printer - thermal line - two-colour (monochrome)
Enclosure Colour:	Cool white

Printer

Print Speed:	Up to 220 mm/sec - max speed
Built-in Devices:	Buzzer
Connectivity Technology:	Wired
Interface:	USB
Max Resolution (B&W):	203 dpi
Language Simulation:	EPSON ESC/POS
Fonts:	3 fonts
Character Sizes (mm):	1 x 2 mm, 1.5 x 3 mm, 1.13 x 3 mm
Columns:	36, 48, 53, 35, 64, 72, 71, 80, 46, 52, 54
Features:	Two-colour thermal printing
Auto Cutter:	Yes

Dimensions & Weight

Width:	14.7 cm
Depth:	20.7 cm
Height:	14.7 cm
Weight:	2 kg

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 90% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Software / System Requirements

Software Included:	Drivers & Utilities
OS Required:	Microsoft Windows Server 2003, Microsoft Windows Vista / 2000 / XP

Power

Printer

Barcodes:	Code 93, Code 39, QR code, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, PDF417, ITF
Printer Features:	Quick-Clear technology, Spill-Shield design

Flash Memory

Flash Memory:	384 KB
---------------	--------

Power

Power Device:	Power supply
Frequency Required:	50/60 Hz
Power Consumption Operational:	70 Watt

Miscellaneous

Features:	Moisture resistant
Compatible with Windows 7:	"Compatible with Windows 7" software and devices carry Microsoft's assurance that these products have passed tests for compatibility and reliability with 32-bit and 64-bit Windows 7.
Compliant Standards:	FCC Class A certified, UL, TUV GS, cUL, OPOS, IEC 60529 IPX1

Expansion / Connectivity

Connections:	1 x USB 1 x cash drawer
--------------	---------------------------

Media Handling

Media Type:	Thermal paper
Max Media Size:	Roll (8.25 cm)
Min Media Size (Custom):	58 mm
Max Media Size (Custom):	82.5 mm
Media Sizes:	Roll (8 cm), Roll (6 cm), Roll (5.8 cm), Roll (8.25 cm)
Max Printing Width:	80 mm
Roll Maximum Outer Diameter:	102 mm
Media Feeders:	1 x manual - 1 roll - Roll (8.25 cm)

