

# CORSAIR SF Series SF750 - power supply - 750 Watt



Not in stock

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| SKU                       | CP-9020186-EU                                     |
| Product Description:      | CORSAIR SF Series SF750 - power supply - 750 Watt |
| Device Type:              | Power supply - internal                           |
| Specification Compliance: | ATX12V 2.4/ EPS12V 2.92 / SFX12V                  |
| 80 PLUS Certification:    | 80 PLUS Platinum                                  |
| Localisation:             | Europe                                            |
| Input Voltage:            | AC 100-240 V                                      |
| Output Voltage:           | +3.3, +5, ±12 V                                   |

## General

|                           |                                  |
|---------------------------|----------------------------------|
| Device Type:              | Power supply - internal          |
| Specification Compliance: | ATX12V 2.4/ EPS12V 2.92 / SFX12V |
| PSU Form Factor:          | SFX                              |
| Localisation:             | Europe                           |

## Dimensions & Weight

|         |         |
|---------|---------|
| Width:  | 12.5 cm |
| Depth:  | 10 cm   |
| Height: | 6.3 cm  |

## Manufacturer Warranty

|                    |                            |
|--------------------|----------------------------|
| Service & Support: | Limited warranty - 7 years |
|--------------------|----------------------------|

## Miscellaneous

|                       |                                                                             |
|-----------------------|-----------------------------------------------------------------------------|
| Included Accessories: | Case badge, cable ties, cable bag, SFX to ATX bracket                       |
| MTBF:                 | 100,000 hours                                                               |
| Cooling System:       | 92 mm fan                                                                   |
| Features:             | Sleeved cables, Zero RPM fan mode, rifle bearing cooling fan, fully modular |

## Power Device

|                     |              |
|---------------------|--------------|
| Input Voltage:      | AC 100-240 V |
| Frequency Required: | 47 - 63 Hz   |



## Power Device

|                                  |                                                                                                                                                                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Output Connectors Details: | 1 x power 24 pin ATX with detachable 4 pin section   2 x power 8 pin EPS12V with detachable 4 pin ATX12V section   4 x 8 pin PCI Express power with detachable 2 pin section   8 x 15 pin Serial ATA power   3 x 4 PIN internal power |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                 |                 |
|-----------------|-----------------|
| Output Voltage: | +3.3, +5, ±12 V |
|-----------------|-----------------|

|                 |          |
|-----------------|----------|
| Power Capacity: | 750 Watt |
|-----------------|----------|

|                 |                                                                          |
|-----------------|--------------------------------------------------------------------------|
| Output Current: | +3.3V - 20 A   +5V - 20 A   +12V - 62.5 A   -12V - 0.3 A   +5VSB - 2.5 A |
|-----------------|--------------------------------------------------------------------------|

|             |     |
|-------------|-----|
| Efficiency: | 92% |
|-------------|-----|

|                           |     |
|---------------------------|-----|
| Modular Cable Management: | Yes |
|---------------------------|-----|

|                        |                  |
|------------------------|------------------|
| 80 PLUS Certification: | 80 PLUS Platinum |
|------------------------|------------------|

