

D-Link DGS 108GL - switch - 8 ports - unmanaged



10-06-2024

SKU	DGS-108GL/E
Product Description:	D-Link DGS 108GL - switch - 8 ports - unmanaged
Device Type:	Switch - 8 ports - unmanaged
Subtype:	Gigabit Ethernet
Ports:	8 x 10/100/1000
Performance:	Switching capacity: 16 Gbps ; Packet filter/forwarding rate (10 Mbps): 14880 pps ; Packet filter/forwarding rate (100 Mbps): 148800 pps ; Packet filter/forwarding rate (1000 Mbps):: 1488000 pps
MAC Address Table Size:	4K entries
Features:	Flow control, auto-uplink (auto MDI/MDI-X), store and forward, QoS, D-Link Green Technology, fanless, metal housing, VoIP support, NAS support, SOHO, EEE



General

Device Type: Switch - 8 ports - unmanaged

Enclosure Type: Desktop

Subtype: Gigabit Ethernet

Ports: 8 x 10/100/1000

Performance: Switching capacity: 16 Gbps | Packet filter/forwarding rate (10 Mbps): 14880 pps | Packet filter/forwarding rate (100 Mbps): 148800 pps | Packet filter/forwarding rate (1000 Mbps):: 1488000 pps

MAC Address Table Size: 4K entries

Features: Flow control, auto-uplink (auto MDI/MDI-X), store and forward, QoS, D-Link Green Technology, fanless, metal housing, VoIP support, NAS support, SOHO, EEE

Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az

Status Indicators: Power, link/activity

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 10 - 90% (non-condensing)

Min Storage Temperature: -10 °C

Max Storage Temperature: 70 °C

Humidity Range Storage: 5 - 95% (non-condensing)

Dimensions & Weight

Width: 14 cm

Depth: 6.7 cm

Height: 2.6 cm

Weight: 240 g

Miscellaneous

MTBF: 1,402,428 hours

Compliant Standards: Plug and Play, FCC, RoHS

Localisation: Europe

Power

Power Device: External power adapter

Power Provided: DC 5 V - 1 A

Power Consumption Operational: 4.31 Watt

Expansion / Connectivity

Interfaces: 8 x 1000Base-T RJ-45

