

# Datalogic Touch TD1100 65 Lite - barcode scanner



Not in stock

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| SKU                      | TD1120-BK-65                                     |
| Product Description:     | Datalogic Touch TD1100 65 Lite - barcode scanner |
| Type:                    | Barcode scanner - handheld - USB - decoded       |
| Colour:                  | Black                                            |
| Minimum Bar Width:       | 4 mil                                            |
| Scan Field Width:        | 15 cm                                            |
| Scan Element Type:       | CCD - Red LED                                    |
| Connectivity Technology: | Wired                                            |

## General

|         |                            |
|---------|----------------------------|
| Type:   | Barcode scanner - handheld |
| Colour: | Black                      |

## Environmental Parameters

|                            |                          |
|----------------------------|--------------------------|
| Min Operating Temperature: | 0 °C                     |
| Max Operating Temperature: | 50 °C                    |
| Humidity Range Operating:  | 5 - 95% (non-condensing) |
| Drop Specification:        | 1.5 m to concrete        |

## Manufacturer Warranty

|                    |                            |
|--------------------|----------------------------|
| Service & Support: | Limited warranty - 5 years |
|--------------------|----------------------------|

## Dimensions & Weight

|         |        |
|---------|--------|
| Width:  | 5.8 cm |
| Depth:  | 8.4 cm |
| Height: | 16 cm  |
| Weight: | 130 g  |

## Software

|                    |                                                              |
|--------------------|--------------------------------------------------------------|
| Software Included: | Drivers & Utilities, Datalogic Aladdin, OPOS/JavaPOS Drivers |
|--------------------|--------------------------------------------------------------|

## Power

|                            |                                   |
|----------------------------|-----------------------------------|
| Electric Current Required: | 20 mA (standby), 100 mA (typical) |
|----------------------------|-----------------------------------|

## Miscellaneous

Cables Included: No data cable is included

Compliant Standards: RoHS, JavaPOS, IP30

## Expansion / Connectivity

Interfaces: 1 x USB

## Barcode

Interface Type: USB

Minimum Bar Width: 4 mil

Scan Field Width: 15 cm

Scan Element Type: CCD - Red LED

Light Source Wave Length: 640 nm

Scan Mode: Single-pass

Skew (Degrees): 70

Pitch (Degrees): 65

Print Contrast Signal (PCS): 25%

Decode Capability: Code 93, Industrial 2 of 5, Code 39, ISBT 128, IATA, GS1 DataBar, BC 412, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Code 11, Interleaved 2 of 5, Codablock F, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Standard 2 of 5, GS1 DataBar Stacked

TTL Decoding: Decoded

Connectivity Technology: Wired

OK Notification: Beeper, LED indicator

## Barcode

### Features:

ESD (electrostatic discharge) safe

