

Dell PowerEdge R360 - rack-mountable Xeon E-2414 2.6 GHz - 16 GB - SSD 480 GB



Not in stock

SKU	4V57T
Product Description:	Dell PowerEdge R360 - rack-mountable Xeon E-2414 2.6 GHz - 16 GB - SSD 480 GB
Type:	Server - rack-mountable
Bundled Services:	3 Years Dell ProSupport
Height (Rack Units):	1U
Server Scalability:	1-way
Processor:	1 x Intel Xeon E-2414 / 2.6 GHz (up to 4.5 GHz, (Quad-Core))
Cache Memory:	12 MB

General

Type:	Server
Bundled Services:	3 Years Dell ProSupport
Product Form Factor:	Rack-mountable - 1U
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Server Scalability:	1-way
Hot-Swap Bays Qty:	4

Processor / Chipset

CPU:	Intel Xeon E-2414
Clock Speed:	2.6 GHz
Max Turbo Speed:	4.5 GHz
Number of Cores:	Quad-Core
CPU Qty:	1
Max CPU Qty:	1

Cache Memory

Installed Size:	12 MB
-----------------	-------

Dimensions & Weight

Width:	48.2 cm
Depth:	59.89 cm
Height:	4.28 cm

Sustainability Information

Carbon Footprint:	1140 kg carbon emissions
Total CF/unit Standard Deviation (kg CO2e):	943
Manufacturing (kg CO2e):	308
Logistics (kg CO2e):	103
Use (kg CO2e):	718
EOL (kg CO2e):	11
Total Carbon w/o Use Phase (kg CO2e):	422
PAIA Version:	1.4.0, 2024

Operating System / Software

OS Provided:	No operating system
--------------	---------------------

Power

Produktdatablad genereret d. 16-09-2024 21:53.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

Cache Memory

Cache Per Processor: 12 MB

RAM

Installed Size: 16 GB (installed) / 128 GB (max)

Technology: DDR5 SDRAM - ECC

Effective Memory Speed: 4800 MHz

Rated Memory Speed: 4800 MHz

Form Factor: DIMM 288-pin

Slots: 4 (Total) / 3 (empty)

Features: Unbuffered

Configuration Features: 1 x 16 GB

Hard Drive

Type: SSD - hot-swap - 2.5"

Capacity: 1 x 480 GB

Interface Type: SATA 6Gb/s

Features: 1 DWPD, Read Intensive, advanced format 512

Storage Controller

Type: 1

Storage Controller Name: PERC H355 Front

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Graphics Processor: Matrox G200eW

Video Memory: 16 MB

Video Interfaces: VGA

Power

Device Type: Power supply - hot-plug

Power Redundancy: Optional

Power Redundancy Scheme: 1+1 (with optional power supply)

Installed Qty: 1

Max Supported Qty: 2

Voltage Required: AC 200-240 V

Power Provided: 700 Watt

80 PLUS Certification: 80 PLUS Titanium

Miscellaneous

Included Accessories: Bezel, ReadyRails sliding rails without cable management arm, power cord (2m, 10A, C13 to C14)

Pricing Type: Build To Plan (BTP)

Manufacturer Selling Program: Dell Smart Selection, Dell Smart Value

Expansion / Connectivity

Bays: 4 (total) / 3 (free) x hot-swap 3.5" ; 1 (total) / 1 (free) x external 5.25" Slim Line

Interfaces: 2 x LAN (Gigabit Ethernet) ; 2 x USB 2.0 (1 front, 1 rear) ; 1 x VGA (1 rear) ; 1 x management - micro-USB Type-AB (1 in front) (iDRAC Direct port) ; 2 x USB 3.2 Gen 1 (1 rear, 1 internal) ; 1 x serial

Networking

Interface (Bus) Type: LAN-on-motherboard (LOM)

Ethernet Ports: 2 x Gigabit Ethernet

Ethernet Controller: Broadcom BCM5720

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Remote Management Controller: Integrated Dell Remote Access Controller 9 Enterprise 16G