

Dell UltraSharp U2722D - LED monitor - QHD - 27"



Not in stock

SKU	DELL-U2722D
Product Description:	Dell UltraSharp U2722D - LED monitor - QHD - 27"
Device Type:	LED-backlit LCD monitor - 27"
Energy Class:	Class E
Power Consumption (On mode):	20 W
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	QHD 2560 x 1440 at 60 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class E
Diagonal Size:	27"
Panel Type:	IPS
Aspect Ratio:	16:9
Native Resolution:	QHD 2560 x 1440 at 60 Hz
Pixel Pitch:	0.2331 mm
Pixel Per Inch:	108.78
Brightness:	350 cd/m ²
Contrast Ratio:	1000:1
Colour Support:	1.07 billion colours
Colour Gamut:	100% Rec 709, 100% sRGB, 95% DCI-P3
Response Time:	5 ms (fast), 8 ms (normal)
Vertical Refresh Rate:	49 - 76 Hz
Horizontal Refresh Rate:	30 - 90 kHz

Compatibility Information

Designed For:	Dell Latitude 5320, 5520 Dell OptiPlex 3090 Dell Precision 7560
---------------	---

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Premium Panel Guarantee
Bundled Services:	3 years Basic Hardware Service with Advanced Exchange

Sustainability Information

TCO Certified:	TCO Certified Displays 9
ENERGY STAR Certified:	Yes

Dimensions & Weight (Shipping)

Shipping Weight:	9.62 kg
------------------	---------

Dimensions & Weight

General

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, 3H Hard Coating

Backlight Technology: LED backlight

Features: Picture by picture, OSD lock, integrated cable management, Flicker Free technology, Mercury free, arsenic-free glass, Dell Easy Arrange, Low Blue Light technology, Delta E<2 calibration

Dimensions (WxDxH): 61.134 cm x 18.5 cm x 38.513 cm - with stand

Connectivity

Interfaces: HDMI | DisplayPort 1.4 (HDCP 1.4) | DisplayPort output | USB-C 3.2 Gen 2 upstream | USB-C 3.2 Gen 2 downstream (power up to 15W) | 2 x USB 3.2 Gen 2 downstream | USB 3.2 Gen 2 downstream with Battery Charging 1.2 | Audio line-out (mini-jack)

Mechanical

Display Position Adjustments: Height, pivot (rotation), swivel, tilt

Tilt Angle: -5/+21

Swivel Angle: 90

Rotation Angle: 180

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

Dimensions & Weight

Dimensions & Weight Details: With stand - width: 61.134 cm - depth: 18.5 cm - height: 38.513 cm | Without stand - width: 61.134 cm - depth: 4.95 cm - height: 35.201 cm - weight: 4.38 kg

Power

Input Voltage: AC 120/230 V (50/60 Hz)

Power Consumption (On mode): 20 W

Power Consumption SDR (On mode): 20 kWh/1000h

Power Consumption (Typical): 20 Watt

Power Consumption (Max): 74 Watt

Power Consumption Stand by: 0.3 Watt

Power Consumption (Off Mode): 0.3 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately)

Cables Included: 1 x DisplayPort cable - DisplayPort to DisplayPort - 1.8 m | 1 x SuperSpeed USB cable - USB Type C to A - 1 m

Compliant Standards: Plug and Play, RoHS, NFPA 99, TUV Rheinland, BFR-free, DisplayPort 1.4, HDCP 1.4, PVC-free

Security Slot Type: Kensington security slot