

Emulex LPe31000-M6-D - host bus adapter - PCIe 3.0 x8 - 16Gb Fibre Channel x 1



Not in stock

SKU	403-BBLZ
Product Description:	Emulex LPe31000-M6-D - host bus adapter - PCIe 3.0 x8 - 16Gb Fibre Channel x 1
Device Type:	Host bus adapter
Form Factor:	Plug-in card - low profile
Interface (Bus) Type:	PCI Express 3.0 x8
PCI Specification Revision:	PCIe 3.0
Ports:	16Gb Fibre Channel x 1
Cabling Type:	Fibre optic

General

Device Type:	Host bus adapter
Form Factor:	Plug-in card - low profile
Interface (Bus) Type:	PCI Express 3.0 x8
PCI Specification Revision:	PCIe 3.0

Compatibility Information

Designed For:	Dell PowerEdge C4130, FC630, FC830
---------------	------------------------------------

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	55 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Software / System Requirements

OS Required:	SUSE Linux Enterprise Server, Microsoft Windows, Red Hat Enterprise Linux
--------------	---

Miscellaneous

Compliant Standards:	CSA, UL, FCC, RoHS, TUV Bauart, BSMI Class A, ICES Class A, VCCI Class A, MSIP Class A, China RoHS, RCM
Pricing Type:	Customer-replaceable Unit (CRU)

Expansion / Connectivity

Interfaces:	1 x 16Gb Fibre Channel
-------------	------------------------

Networking

Ports:	16Gb Fibre Channel x 1
Connectivity Technology:	Wired
Cabling Type:	Fibre optic
Data Link Protocol:	16Gb Fibre Channel
Fibre Channel:	FC-DA, FC-FS, FC-GS-2, FC-GS-3, FC-GS-4, FC-MI, FC-PH-2, FC-PH-3, FC-PI, FC-Tape, FCP-4, FCP-2, FC-PI-2, FC-GS-5, FCP-3, FC-PI-4, FC-FS-3, FC-GS-6, FC-PI-3, FC-HBA, FC-PI-5, FC-LS-2, FC-DA-2, SSC-2, SBC-2, SPC-3, FC-PI-6, SBC-3, SPC-4, SSC-4
Data Transfer Rate:	14.025 Gbps
Features:	FEC

