

# Eaton Ellipse ECO 500 DIN - UPS - 300 Watt - 500 VA



Not in stock

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| SKU                  | EL500DIN                                            |
| Product Description: | Eaton Ellipse ECO 500 DIN - UPS - 300 Watt - 500 VA |
| Device Type:         | UPS - rack-mountable / external                     |
| Rack Size:           | 19" - 2U                                            |
| Weight:              | 2.9 kg                                              |
| Input Voltage:       | AC 230 V                                            |
| Output Voltage:      | AC 220/230/240 V                                    |
| Power Capacity:      | 300 Watt / 500 VA                                   |

## General

|                      |                                 |
|----------------------|---------------------------------|
| Device Type:         | UPS - rack-mountable / external |
| Height (Rack Units): | 2U                              |
| Rack Size:           | 19"                             |

## Dimensions & Weight

|         |         |
|---------|---------|
| Width:  | 8.1 cm  |
| Depth:  | 23.5 cm |
| Height: | 26.3 cm |
| Weight: | 2.9 kg  |

## Power Device

|                                   |                                  |
|-----------------------------------|----------------------------------|
| UPS Technology:                   | Off-line                         |
| Input Voltage:                    | AC 230 V                         |
| Input Voltage Range:              | AC 184 - 264 V                   |
| Input Voltage Range (Adjustable): | AC 161 - 284 V                   |
| Frequency Provided:               | 50/60 Hz                         |
| Frequency Required:               | 50/60 Hz                         |
| Input Connectors:                 | 1 x power                        |
| Power Output Connectors Details:  | 3 (UPS and surge) ; 1 (surge)    |
| Output Voltage:                   | AC 220/230/240 V 50/60 Hz        |
| Power Capacity:                   | 300 Watt / 500 VA                |
| Dataline Surge Protection:        | Network/phone line - RJ-45/RJ-11 |
| Surge Suppression:                | Yes                              |
| Circuit Protection:               | Circuit breaker                  |

## Manufacturer Warranty

|                    |                            |
|--------------------|----------------------------|
| Service & Support: | Limited warranty - 2 years |
|--------------------|----------------------------|

## Miscellaneous

|                      |                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------|
| Rack Mounting Kit:   | Optional                                                                                      |
| Features:            | Wall mountable, audible alarm, LED indicators, deep discharge protection, cold-start function |
| Compliant Standards: | CB, IEC 62040-1-1, IEC 62040-2, IEC 60950-1, IEC 61643-1                                      |

## Battery

|                   |                                        |
|-------------------|----------------------------------------|
| Technology:       | Lead Acid                              |
| Run Time (Up To): | 9 min at half load ; 5 min at 70% load |