

Eaton Ellipse PRO 1200 - UPS - 750 Watt - 1200 VA



Not in stock

SKU	ELP1200DIN
Product Description:	Eaton Ellipse PRO 1200 - UPS - 750 Watt - 1200 VA
Device Type:	UPS - external
Rack Size:	19" - 2U
Weight:	9.9 kg
Input Voltage:	AC 230 V
Output Voltage:	AC 220/230/240 V + 15% / - 20%
Power Capacity:	750 Watt / 1200 VA



General

Device Type:	UPS - external
Height (Rack Units):	2U
Rack Size:	19"

Power Device

UPS Technology:	Line interactive
Input Voltage:	AC 230 V
Input Voltage Range:	AC 165 - 285 V
Input Voltage Range (Adjustable):	AC 150 - 285 V
Frequency Provided:	50/60 Hz
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60320 C14
Power Output Connectors Details:	4 x power CEE 7/7 (UPS and surge) ; 4 x power CEE 7/7 (surge)
Output Voltage:	AC 220/230/240 V + 15% / - 20% - 50/60 Hz
Power Capacity:	750 Watt / 1200 VA
Dataline Surge Protection:	Network/phone line - RJ-45/RJ-11 - 1 input line / 1 output line
Surge Suppression:	Yes
Circuit Protection:	Circuit breaker

Battery

Quantity:	2
Technology:	Lead Acid
Capacity:	7 Ah
Run Time (Up To):	9 min at half load ; 5 min at 70% load

Networking

Remote Management Interface:	USB
------------------------------	-----

Dimensions & Weight

Width:	8.2 cm
Depth:	39 cm
Height:	27.5 cm
Weight:	9.9 kg

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	0 - 85%

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years ; Limited warranty - batteries - 3 years
--------------------	---

Software / System Requirements

Software Included:	Eaton UPS Companion
--------------------	---------------------

Miscellaneous

Cables Included:	USB cable - external
Rack Mounting Kit:	Optional
Features:	Wall mountable, LCD display, Automatic Voltage Regulation (AVR), deep discharge protection, cold-start function, EcoControl Master/Control outlets
Compliant Standards:	CB, IEC 62040-1-1, IEC 62040-2, IEC 61643-1, EN 62040-1-1, EN 62040-2

Expansion / Connectivity

Interfaces:	1 x management (USB) - 4 pin USB Type B
-------------	---