

Elo 1515L IntelliTouch - LCD monitor - 15"



10-05-2024

SKU	E399324
Product Description:	Elo 1515L IntelliTouch - LCD monitor - 15"
Device Type:	LCD monitor - 15" - touchscreen
Features:	Touch-screen
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 75 Hz
Brightness:	225 cd/m ²
Contrast Ratio:	500:1

General

Display Type:	LCD monitor / TFT active matrix
Diagonal Size:	15"
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 75 Hz
Brightness:	225 cd/m ²
Contrast Ratio:	500:1
Colour Support:	16.7 million colours
Response Time:	11.7 ms
Vertical Refresh Rate:	75 Hz
Horizontal Refresh Rate:	60.2 kHz
Horizontal Viewing Angle:	+65 / -65
Vertical Viewing Angle:	+55 / -65
Screen Coating:	Anti-glare
Controls & Adjustments:	Brightness, contrast, H/V position, colour temperature, phase, clock
OSD Languages:	English, German, French, Spanish, Japanese
Features:	IntelliTouch Surface Wave, Sync on Green

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80%

Power

Power Supply:	Internal
Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (Typical):	30 Watt

Miscellaneous

Features:	Security lock slot (cable lock sold separately), wall mountable
Cables Included:	1 x VGA cable 1 x serial cable 1 x USB cable
Backlight Life:	30,000 hours
MTBF:	50,000 hour(s)
Compliant Standards:	UL, VCCI, C-Tick, cUL, MPR III, SEMKO, IC, FCC, RoHS

Mechanical

VESA Mounting Interface:	75 x 75 mm
--------------------------	------------

Connectivity

General

Colour: Dark grey

Dimensions (WxDxH): 35 cm x 17.5 cm x 31 cm

Weight: 4.8 kg

Input

Type: Touch-screen -
touchscreen

Movement Detection
Technology: Surface acoustic wave

Connectivity

1 x VGA - 15 pin HD D-Sub (HD-15) ; 1 x
Interfaces: serial RS-232 - 9 pin D-Sub (DB-9) ; 1 x USB
- 4 pin USB Type B

