

Elo 1517L iTouch Zero-Bezel - LED monitor - 15"



In Stock(141)

SKU	E829550
Product Description:	Elo 1517L iTouch Zero-Bezel - LED monitor - 15"
Device Type:	LED-backlit LCD monitor - 15" - touchscreen
Features:	Touch-screen
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 75 Hz
Brightness:	300 cd/m²
Contrast Ratio:	800:1



General

Display Type: LED-backlit LCD monitor / TFT active matrix

Diagonal Size: 15"

Aspect Ratio: 4:3

Native Resolution: 1024 x 768 at 75 Hz

Brightness: 300 cd/m²

Brightness w/touchscreen: 270 cd/m²

Contrast Ratio: 800:1

Colour Support: 16.2 million colours

Response Time: 23 ms

Horizontal Viewing Angle: +80 / -80

Vertical Viewing Angle: +70 / -70

Backlight Technology: LED backlight

Controls & Adjustments: Brightness, contrast, H/V position, sharpness, colour balance, colour temperature, phase, clock, aspect control

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese

Features: iTouch Surface Wave

Colour: Black

Dimensions (WxDxH): 35.8 cm x 19.7 cm x 31.9 cm - with stand

Weight: 4.3 kg

Input

Type: Touch-screen - touchscreen

Movement Detection Technology: Surface acoustic wave

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support: Limited warranty - 3 years

Power

Input Voltage: AC 120/230 V (50/60 Hz)

Power Consumption (Typical): 10.5 Watt

Power Consumption Stand by: 0.92 Watt

Power Consumption Sleep: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), iTouch Surface Acoustic Wave Technology

MTBF: 50,000 hour(s)

Compliant Standards: UL, VCCI, C-Tick, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, S Mark, China RoHS

Localisation: Worldwide

Mechanical

VESA Mounting Interface: 75 x 75 mm

Connectivity

Interfaces: Serial | USB | VGA