

Elo 1523L - LED monitor - 15"



In Stock(88)

SKU	E738607
Product Description:	Elo 1523L - LED monitor - 15"
Device Type:	LED-backlit LCD monitor - 15" - touchscreen
Features:	Touch-screen, USB Hub
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 75 Hz
Brightness:	250 cd/m ²
Contrast Ratio:	700:1

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Diagonal Size:	15"
Built-in Devices:	USB Hub
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 75 Hz
Brightness:	250 cd/m ²
Brightness w/touchscreen:	215 cd/m ²
Contrast Ratio:	700:1
Colour Support:	16.2 million colours
Response Time:	25 ms
Vertical Refresh Rate:	56 - 75 Hz
Horizontal Refresh Rate:	31 - 80 KHz
Horizontal Viewing Angle:	160
Vertical Viewing Angle:	140
Backlight Technology:	LED backlight

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Dimensions & Weight

Dimensions & Weight Details:	Without stand - weight: 2.65 kg
------------------------------	---------------------------------

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (Typical):	12 Watt

Miscellaneous

Features:	Security lock slot (cable lock sold separately)
MTBF:	50,000 hour(s)
Compliant Standards:	UL, VCCI, C-Tick, BSMI, cUL, VESA DPMS, CB, CCC, IC, FCC, RoHS, DDC, KCC, WEEE, E-Standby, China RoHS, CoC
Security Slot Type:	Kensington security slot

General

Controls & Adjustments:

Mute, volume, brightness, contrast, H/V position, sharpness, colour temperature, phase, clock, aspect control

OSD Languages:

Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese

Features:

Anti-glare, Projected Capacitive Touch (P-CAP) technology

Colour:

Black

Dimensions (WxDxH):

35.8 cm x 31.8 cm x 19.9 cm - with stand

Weight:

4.44 kg

Audio

Type:

Speakers - stereo

Output Power / Channel:

2 Watt

Mechanical

Display Position Adjustments:

Tilt

VESA Mounting Interface:

75 x 75 mm

Connectivity

Interfaces:

VGA | DVI-D | 2 x USB

Input

Type:

Touch-screen - touchscreen

Movement Detection Technology:

Projected capacitive

