

Elo 1590L - 90-Series - LED monitor - 15"



02-05-2024

SKU	E334335
Product Description:	Elo 1590L - 90-Series - LED monitor - 15"
Device Type:	LED-backlit LCD monitor - 15" - touchscreen
Energy Class:	Class B
Energy Consumption per Year:	21 kWh
Power Consumption (On mode):	14 W
Features:	Touch-screen
Aspect Ratio:	4:3

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class B
Energy Consumption per Year:	21 kWh
Diagonal Size:	15"
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 75 Hz
Brightness:	250 cd/m ²
Brightness w/touchscreen:	225 cd/m ²
Contrast Ratio:	700:1
Colour Support:	16.2 million colours
Response Time:	16 ms (tr - tf)
Vertical Refresh Rate:	50 - 75 Hz
Horizontal Refresh Rate:	30 - 60 kHz
Horizontal Viewing Angle:	+80 / -80
Vertical Viewing Angle:	+70 / -70
Backlight Technology:	LED backlight

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Power Consumption (On mode):	14 W
Power Consumption (Typical):	12.5 Watt
Power Consumption Sleep:	1.5 Watt
Power Consumption (Off Mode):	0.5 Watt

Miscellaneous

Cables Included:	1 x USB cable ; 1 x VGA cable ; 1 x HDMI cable
Mounting Kit:	Included
MTBF:	50,000 hours
Compliant Standards:	UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, IMERC

Produktdatablad genereret d. 02-05-2024 11:57.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

Features: Remote OSD, Projected Capacitive Touch (P-CAP) technology

Colour: Black

Dimensions (WxDxH): 35.8 cm x 3.56 cm x 28.49 cm

Weight: 2.9 kg

Input

Type: Touch-screen - touchscreen

Movement Detection Technology: Projected capacitive

Miscellaneous

Localisation: Worldwide

Mechanical

VESA Mounting Interface: 100 x 100 mm, 75 x 75 mm

Connectivity

Interfaces: VGA | DisplayPort | USB (Type B) | Management (RJ-45) | HDMI

