

Elo 1590L - 90-Series - LED monitor - 15"



02-05-2024

SKU	E334530
Product Description:	Elo 1590L - 90-Series - LED monitor - 15"
Device Type:	LED-backlit LCD monitor - 15" - touchscreen
Energy Class:	Class B
Energy Consumption per Year:	21 kWh
Power Consumption (On mode):	14 W
Features:	Touch-screen
Aspect Ratio:	4:3



General

Display Type: LED-backlit LCD monitor / TFT active matrix

Energy Class: Class B

Energy Consumption per Year: 21 kWh

Diagonal Size: 15"

Aspect Ratio: 4:3

Native Resolution: 1024 x 768 at 75 Hz

Brightness: 250 cd/m²

Brightness w/touchscreen: 220 cd/m²

Contrast Ratio: 700:1

Colour Support: 16.2 million colours

Response Time: 16 ms (tr - tf)

Vertical Refresh Rate: 50 - 75 Hz

Horizontal Refresh Rate: 30 - 60 kHz

Horizontal Viewing Angle: +80 / -80

Vertical Viewing Angle: +70 / -70

Screen Coating: Anti-glare

Backlight Technology: LED backlight

Features: Remote OSD, SecureTouch Surface Wave

Colour: Black

Dimensions (WxDxH): 33.64 cm x 4.19 cm x 26.44 cm

Weight: 2.9 kg

Input

Type: Touch-screen - touchscreen

Movement Detection Technology: Surface acoustic wave

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support: Limited warranty - 3 years

Power

Power Consumption (On mode): 14 W

Power Consumption (Typical): 12.5 Watt

Power Consumption Sleep: 1.5 Watt

Power Consumption (Off Mode): 0.5 Watt

Miscellaneous

Cables Included: 1 x USB cable ; 1 x VGA cable ; 1 x HDMI cable

Mounting Kit: Included

MTBF: 50,000 hours

Compliant Standards: UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, IMERC

Localisation: Worldwide

Mechanical

VESA Mounting Interface: 100 x 100 mm, 75 x 75 mm

Connectivity

Interfaces: VGA ; DisplayPort ; USB (Type B) ; Management (RJ-45) ; HDMI ; Serial (DB-9)