

Elo 1598L - Rev A - LED monitor - 15"



02-05-2024

SKU	E126407
Product Description:	Elo 1598L - Rev A - LED monitor - 15"
Device Type:	LED-backlit LCD monitor - 15" - touchscreen
Energy Class:	Class B
Energy Consumption per Year:	23 kWh
Power Consumption (On mode):	16 W
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 60 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class B
Energy Consumption per Year:	23 kWh
Diagonal Size:	15"
Aspect Ratio:	4:3
Native Resolution:	1024 x 768 at 60 Hz
Brightness:	500 cd/m ²
Brightness w/touchscreen:	400 cd/m ²
Contrast Ratio:	1500:1
Colour Support:	16.2 million colours
Response Time:	35 ms
Vertical Refresh Rate:	50 - 75 Hz
Horizontal Refresh Rate:	30 - 60 kHz
Horizontal Viewing Angle:	+85 / -85
Vertical Viewing Angle:	+85 / -85

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Input Voltage:	AC 100 - 240 V (50/60 Hz)
Power Consumption (On mode):	16 W
Power Consumption (Typical):	14.1 Watt
Power Consumption Sleep:	1.5 Watt
Power Consumption (Off Mode):	0.5 Watt

Miscellaneous

Included Accessories:	Remote control
Cables Included:	1 x HDMI cable 1 x USB cable 1 x VGA cable

General

Backlight Technology: LED backlight

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese

Features: AccuTouch Five-Wire Resistive

Colour: Black

Dimensions (WxDxH): 33.64 cm x 4.19 cm x 26.44 cm

Weight: 2.9 kg

Input

Type: Touchscreen

Miscellaneous

Mounting Kit: Included

MTBF: 50,000 hours

Compliant Standards: UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, IMERC

Connectivity

Interfaces: HDMI ; VGA (DB-15) ; DisplayPort ; Serial (DB-9) ; USB ; Management

