

Elo 1723L - LED monitor - 17"



In Stock(2)

SKU	E016808
Product Description:	Elo 1723L - LED monitor - 17"
Device Type:	LED-backlit LCD monitor - 17" - touchscreen
Features:	Touch-screen, USB Hub
Aspect Ratio:	5:4
Native Resolution:	1280 x 1024 at 75 Hz
Brightness:	250 cd/m ²
Contrast Ratio:	800:1

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Diagonal Size:	17"
Built-in Devices:	USB Hub
Aspect Ratio:	5:4
Native Resolution:	1280 x 1024 at 75 Hz
Brightness:	250 cd/m ²
Brightness w/touchscreen:	215 cd/m ²
Contrast Ratio:	800:1
Colour Support:	16.7 million colours
Response Time:	30 ms
Vertical Refresh Rate:	56 - 75 Hz
Horizontal Refresh Rate:	31 - 80 KHz
Horizontal Viewing Angle:	170
Vertical Viewing Angle:	160
Backlight Technology:	LED backlight

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Dimensions & Weight

Without stand - width: 39.19 cm - depth: 4.95 cm - height: 32.72 cm - weight: 3.56 kg
With stand - width: 39.19 cm - depth: 20.94 cm - height: 36.07 cm - weight: 5.21 kg

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (Typical):	22 Watt
Power Consumption Sleep:	2 Watt

Miscellaneous

Features:	Security lock slot (cable lock sold separately)
Included Accessories:	Cable management clip

General

Controls & Adjustments:	Mute, volume, brightness, contrast, H/V position, sharpness, colour temperature, phase, clock, aspect control
OSD Languages:	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features:	Anti-glare, IntelliTouch Pro
Colour:	White
Dimensions (WxDxH):	39.19 cm x 20.94 cm x 36.07 cm - with stand
Weight:	5.21 kg

Audio

Type:	Speakers - stereo
Output Power / Channel:	2 Watt

Input

Type:	Touch-screen - touchscreen
Movement Detection Technology:	Projected capacitive

Connectivity

Interfaces:	VGA DVI-D 2 x USB (Type A) USB (Type B) USB upstream (Type B)
-------------	---

Miscellaneous

Cables Included:	1 x VGA cable - VGA to VGA 1 x DVI cable - DVI-D to DVI-D 1 x audio cable 1 x USB cable - USB Type A to B
MTBF:	50,000 hour(s)
Compliant Standards:	Plug and Play, UL, VCCI, C-Tick, BSMI, cUL, VESA DPMS, CB, CCC, IC, FCC, RoHS, KCC, WEEE, E-Standby, China RoHS, CoC

Mechanical

Display Position Adjustments:	Height, tilt
Tilt Angle:	-5/+90
VESA Mounting Interface:	75 x 75 mm

