

Elo 1902L - LCD monitor - 19"



In Stock(42)

SKU	E351388
Product Description:	Elo 1902L - LCD monitor - 19"
Device Type:	LCD monitor - 19" - touchscreen
Features:	Touch-screen, USB Hub
Aspect Ratio:	5:4
Native Resolution:	1280 x 1024 at 60 Hz
Brightness:	250 cd/m²
Contrast Ratio:	1000:1

General

Display Type:	LCD monitor / TFT active matrix
Diagonal Size:	19"
Built-in Devices:	USB Hub
Aspect Ratio:	5:4
Native Resolution:	1280 x 1024 at 60 Hz
Brightness:	250 cd/m²
Brightness w/touchscreen:	235 cd/m²
Contrast Ratio:	1000:1
Colour Support:	16.7 million colours
Response Time:	14 ms (tr - tf)
Vertical Refresh Rate:	50 - 75 Hz
Horizontal Refresh Rate:	30 - 82 kHz
Horizontal Viewing Angle:	+89 / -89
Vertical Viewing Angle:	+89 / -89
OSD Languages:	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Russian, Spanish, Japanese, Korean
Features:	TouchPro technology
Colour:	Black

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Dimensions & Weight (Shipping)

Shipping Width:	48.2 cm
Shipping Depth:	26 cm
Shipping Height:	52.7 cm
Shipping Weight:	9.8 kg

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (Typical):	18 Watt
Power Consumption Sleep:	0.8 Watt

Miscellaneous

Included Accessories:	3 cable ties
-----------------------	--------------

General

Dimensions (WxDxH): 42.96 cm x 19.34 cm x 39.77 cm - with stand

Weight: 6.3 kg

Audio

Type: Speakers - stereo

Output Power / Channel: 2 Watt

Input

Type: Touch-screen - touchscreen

Movement Detection Technology: Projected capacitive

Miscellaneous

Cables Included: 1 x VGA cable ; 1 x HDMI cable ; 1 x USB cable ; 1 x audio cable

MTBF: 50,000 hours

Compliant Standards: UL, VCCI, BSMI, cUL, CB, CCC, IC, FCC, KCC, IPX1, EAC, RCM, CoC

Mechanical

VESA Mounting Interface: 100 x 100 mm

Connectivity

Interfaces: HDMI ; VGA ; Headphones ; USB (Type B) ; USB 2.0 (Type A) ; 4 x Micro-USB

