

Elo 1915L IntelliTouch - LED monitor - 19"



02-07-2024

SKU	E266835
Product Description:	Elo 1915L IntelliTouch - LED monitor - 19"
Device Type:	LED-backlit LCD monitor - 19" - touchscreen
Features:	Touch-screen
Native Resolution:	1280 x 1024 at 75 Hz
Brightness:	225 cd/m²
Contrast Ratio:	1000:1
Response Time:	5 ms

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Diagonal Size:	19"
Native Resolution:	1280 x 1024 at 75 Hz
Brightness:	225 cd/m²
Contrast Ratio:	1000:1
Colour Support:	16.7 million colours
Response Time:	5 ms
Vertical Refresh Rate:	56.3 - 75 Hz
Horizontal Refresh Rate:	31.5 - 80 kHz
Horizontal Viewing Angle:	+85 / -85
Vertical Viewing Angle:	+80 / -80
Backlight Technology:	LED backlight
Controls & Adjustments:	Brightness, contrast, H/V position, colour temperature, phase, clock
OSD Languages:	English, German, French, Spanish, Japanese
Features:	IntelliTouch Surface Wave, anti-glare, OSD lock

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80%

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Dimensions & Weight (Shipping)

Shipping Width:	54 cm
Shipping Depth:	28.5 cm
Shipping Height:	49.5 cm
Shipping Weight:	11.7 kg

Power

Power Supply:	Internal
Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (Typical):	23 Watt
Power Consumption Sleep:	1.19 Watt
Power Consumption (Off Mode):	0.63 Watt

Miscellaneous

General

Colour:	Dark grey
Dimensions (WxDxH):	42.9 cm x 20.7 cm x 37.9 cm
Weight:	7.9 kg

Input

Type:	Touch-screen - touchscreen
Movement Detection Technology:	Intellitouch SAW

Connectivity

Interfaces:	VGA Serial USB
Interfaces:	1 x VGA - 15 pin HD D-Sub (HD-15) 1 x serial RS-232 - 9 pin D-Sub (DB-9) 1 x USB - 4 pin USB Type A

Mechanical

VESA Mounting Interface:	100 x 100 mm
--------------------------	--------------

Miscellaneous

Features:	Water-resistant, wall mountable, dust-resistant, dirt resistant, Flexible Mounting Profile, mounting holes, security lock
Cables Included:	1 x VGA cable - 1.8 m 1 x USB cable - USB Type A to B - 1.83 m
MTBF:	50,000 hour(s)
Compliant Standards:	FCC Class B certified, IC Class B, UL, TUV GS, VCCI Class B ITE, cUL, C-Tick Class B, RoHS
Localisation:	EMEA, Americas

