

Elo 1991L - 90-Series - LED monitor - 19"



Not in stock

SKU	E335119
Product Description:	Elo 1991L - 90-Series - LED monitor - 19"
Device Type:	LED-backlit LCD monitor - 19" - touchscreen
Energy Class:	Class A
Energy Consumption per Year:	28 kWh
Power Consumption (On mode):	19 W
Features:	Touch-screen
Aspect Ratio:	5:4

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class A
Energy Consumption per Year:	28 kWh
Diagonal Size:	19"
Aspect Ratio:	5:4
Native Resolution:	1280 x 1024 at 60 Hz
Brightness:	250 cd/m ²
Brightness w/touchscreen:	220 cd/m ²
Contrast Ratio:	1000:1
Colour Support:	16.7 million colours
Response Time:	14 ms (tr - tf)
Vertical Refresh Rate:	50 - 75 Hz
Horizontal Refresh Rate:	30 - 82 kHz
Horizontal Viewing Angle:	+89 / -89
Vertical Viewing Angle:	+89 / -89

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Power Consumption (On mode):	19 W
Power Consumption (Typical):	17 Watt
Power Consumption Sleep:	1.5 Watt
Power Consumption (Off Mode):	0.5 Watt

Miscellaneous

Cables Included:	1 x VGA cable 1 x USB cable 1 x HDMI cable
Mounting Kit:	Included
MTBF:	50,000 hours
Compliant Standards:	UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, IMERC

General

Screen Coating: Anti-glare

Backlight Technology: LED backlight

OSD Languages: Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese

Features: Remote OSD, SecureTouch Surface Wave

Colour: Black

Dimensions (WxDxH): 41.47 cm x 5 cm x 34.27 cm

Weight: 4.6 kg

Input

Type: Touch-screen - touchscreen

Movement Detection Technology: Surface acoustic wave

Miscellaneous

Localisation: Worldwide

Mechanical

VESA Mounting Interface: 100 x 100 mm, 75 x 75 mm

Connectivity

Interfaces: USB (Type B) | VGA | DisplayPort | Management (RJ-45) | HDMI | Serial (DB-9)

