

Elo I-Series 4.0 - Value - all-in-one RK3399 - 4 GB - flash 32 GB - LED 15.6"



Not in stock

SKU	E412421
Product Description:	Elo I-Series 4.0 - Value - all-in-one RK3399 - 4 GB - flash 32 GB - LED 15.6"
Type:	Point of sale terminal - all-in-one
Processor:	1 x Rockchip RK3399
RAM:	4 GB
Hard Drive:	Flash 32 GB
Optical Storage:	No optical drive
Card Reader:	Yes

General

Type:	Point of sale terminal
Product Form Factor:	All-in-one
Colour:	White

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80%

Processor / Chipset

CPU:	Rockchip RK3399
CPU Qty:	1
Max CPU Qty:	1

Dimensions & Weight (Shipping)

Shipping Width:	46.5 cm
Shipping Depth:	16 cm
Shipping Height:	33 cm
Shipping Weight:	3.3 kg

RAM

Installed Size:	4 GB
-----------------	------

Dimensions & Weight

Width:	38.97 cm
Depth:	2.23 cm
Height:	24.97 cm
Weight:	1.6 kg

Hard Drive

Type:	Flash
Capacity:	1 x 32 GB

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Optical Storage

Type:	No optical drive
-------	------------------

Card Reader

Type:	Card reader
Supported Flash Memory Cards:	microSD

Operating System / Software

OS Provided:	Android 10
Software:	Google Mobile Services

Monitor

Monitor Type:	LED
Touchscreen:	Yes (10-point multi-touch)
Diagonal Size:	15.6"
Native Resolution:	1920 x 1080 (Full HD)
V-Sync Rate at Max Res.:	60 Hz
Widescreen Display:	Yes
Image Aspect Ratio:	16:9
Horizontal Viewing Angle:	+80 / -80
Vertical Viewing Angle:	+80 / -80
Response Time:	25 ms
Image Brightness:	215 cd/m ²
Image Contrast Ratio:	700:1
Monitor Features:	TouchPro Pro Projected Capacitive (PCAP) technology

Audio Output

Sound Output Mode:	Stereo
--------------------	--------

Camera

Camera:	Yes
Resolution (MP):	5 Megapixel
Resolution:	1920 x 1080
Features:	Autofocus

Audio Input

Type:	Microphone
-------	------------

Power

Device Type:	Power adapter
Voltage Required:	AC 100-240 V (50/60 Hz)
Power Consumption Operational:	10 Watt
Power Consumption Stand by:	0.4 Watt
Power Consumption Sleep:	2.6 Watt

Miscellaneous

Included Accessories:	Power adapter, screw set
VESA Mounting Interface:	75 mm, 100 mm, VESA
Compliant Standards:	UL, VCCI, cUL, CB, IC, MIC, FCC, RCM

Expansion / Connectivity

Interfaces:	1 x USB 3.0 (900 mA) 1 x USB-C 1 x GPIO 1 x LAN (Gigabit Ethernet) 4 x USB 2.0 - micro-USB (support for 1.2 A on one port and 500 mA for the remaining three ports)
-------------	---

Networking

Wireless LAN Supported:	Yes
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, Bluetooth 5.0
Compliant Standards:	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, Bluetooth 5.0