

Elo Open-Frame Touchmonitors 1990L - LED monitor - 19"



In Stock(12)

SKU	E328497
Product Description:	Elo Open-Frame Touchmonitors 1990L - LED monitor - 19"
Device Type:	LED-backlit LCD monitor - 19" - touchscreen
Energy Class:	Class B
Energy Consumption per Year:	34 kWh
Power Consumption (On mode):	23 W
Aspect Ratio:	5:4
Native Resolution:	1280 x 1024 at 60 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class B
Energy Consumption per Year:	34 kWh
Diagonal Size:	19"
Aspect Ratio:	5:4
Native Resolution:	1280 x 1024 at 60 Hz
Brightness:	250 cd/m ²
Brightness w/touchscreen:	225 cd/m ²
Contrast Ratio:	1000:1
Colour Support:	16.7 million colours
Response Time:	5 ms
Vertical Refresh Rate:	50 - 75 Hz
Horizontal Refresh Rate:	30 - 82 kHz
Horizontal Viewing Angle:	+85 / -85
Vertical Viewing Angle:	+80 / -80

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (On mode):	23 W
Power Consumption (Typical):	22 Watt

Miscellaneous

Cables Included:	1 x USB cable ; 1 x VGA cable ; 1 x HDMI cable
Mounting Kit:	Included
MTBF:	50,000 hours

General

Backlight Technology:	LED backlight
OSD Languages:	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features:	Remote OSD, Slim Design, IntelliTouch Surface Acoustic Wave
Colour:	Black
Dimensions (WxDxH):	41.47 cm x 5 cm x 34.27 cm
Weight:	4.6 kg

Miscellaneous

Compliant Standards:	UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, DisplayPort 1.1a, IMERC
----------------------	--

Mechanical

VESA Mounting Interface: 100 x 100 mm, 75 x 75 mm

Connectivity

Interfaces: USB | VGA | DisplayPort | HDMI | Serial

Input

Type: Touchscreen

