

EloPOS System i2 - all-in-one - Celeron J4105 1.5 GHz - 4 GB - SSD 128 GB - LED 15.6"



Not in stock

SKU	E440439
Product Description:	EloPOS System i2 - all-in-one - Celeron J4105 1.5 GHz - 4 GB - SSD 128 GB - LED 15.6"
Type:	Point of sale terminal - all-in-one
Processor:	1 x Intel Celeron J4105 / 1.5 GHz (, up to 2.5 GHz, (Quad-Core)
Cache Memory:	4 MB
Cache Per Processor:	4 MB
RAM:	4 GB (installed) / 8 GB (max) - DDR4 SDRAM - non-ECC
Storage Controller:	SATA (SATA 6Gb/s)

General

Type:	Point of sale terminal
Product Form Factor:	All-in-one
Embedded Security:	Trusted Platform Module (TPM 2.0) Security Chip
Colour:	Black

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Processor / Chipset

CPU:	Intel Celeron J4105
Clock Speed:	1.5 GHz
Max Turbo Speed:	2.5 GHz
Number of Cores:	Quad-Core
CPU Qty:	1
Max CPU Qty:	1

Dimensions & Weight (Shipping)

Shipping Width:	46.2 cm
Shipping Depth:	29.9 cm
Shipping Height:	47 cm
Shipping Weight:	7.3 kg

Cache Memory

Installed Size:	4 MB
Cache Per Processor:	4 MB

Dimensions & Weight

Dimensions & Weight Details:	38.62 cm - 22.12 cm - 36.93 cm - 4.9 kg - with stand 38.62 cm - 7.33 cm - 24.89 cm - 2.9 kg - without stand
Width:	38.62 cm
Depth:	22.12 cm
Height:	36.93 cm
Weight:	4.9 kg

RAM

Installed Size:	4 GB / 8 GB (max)
-----------------	-------------------

RAM

Technology:	DDR4 SDRAM - non-ECC
Effective Memory Speed:	2400 MHz
Rated Memory Speed:	2666 MHz
Form Factor:	SO-DIMM 260-pin
Slots:	2 (Total) / 1 (empty)
Features:	Unbuffered
Configuration Features:	1 x 4 GB

Hard Drive

Type:	SSD - 2.5"
Capacity:	1 x 128 GB
Interface Type:	SATA 6Gb/s
SSD Endurance:	72 TB

Storage Controller

Type:	1 x SATA
Controller Interface Type:	SATA 6Gb/s

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	LED
Touchscreen:	Yes (10-point multi-touch)
Diagonal Size:	15.6"
Native Resolution:	1366 x 768 (HD)
Widescreen Display:	Yes
Image Aspect Ratio:	16:9
Horizontal Viewing Angle:	90
Vertical Viewing Angle:	50
Response Time:	10 ms
Image Brightness:	220 cd/m ²
Image Contrast Ratio:	400:1
Monitor Features:	Anti-glare, TouchPro technology

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Operating System / Software

OS Provided:	No operating system
--------------	---------------------

Power

Device Type:	Power adapter
Installed Qty:	1
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Provided:	180 Watt
Power Consumption Operational:	24 Watt

Miscellaneous

Cables Included:	RJ-45 to DB-9 cable Power cable (2 pcs.)
VESA Mounting Interface:	75 mm
Compliant Standards:	UL, TUV, VCCI, cUL, NOM, CB, CCC, FCC, S Mark, RCM, CE/EMC

Expansion / Connectivity

Bays:	1 (total) / 0 (free) x internal 2.5" x 1/8H
Interfaces:	3 x USB 3.0 2 x USB 2.0 4 x USB 2.0 - micro-USB 2 x PoweredUSB (12 V) 1 x PoweredUSB (24 V) 1 x LAN (Gigabit Ethernet) - RJ-45 1 x cash drawer 1 x headphones 2 x serial - RJ-45 1 x USB-C (27 Watt charging)

Networking

Wireless LAN Supported:	Yes
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, Bluetooth 5.0

Audio Output

Graphics Controller

Graphics Processor: Intel UHD Graphics 600

Audio Output

Sound Output Mode: Stereo

Speakers Included: 2 x right / left channel

