

Epson EB-685Wi - 3LCD projector - LAN - grey, white



In Stock(54)

SKU	V11H741040
Product Description:	Epson EB-685Wi - 3LCD projector - LAN - grey, white
Device Type:	3LCD projector - 720p
Colour:	Grey, white
Built-in Devices:	Speaker
Brightness (White):	3500 lumens
Brightness (Colour):	3500 lumens
Contrast Ratio:	300:1 / 14000:1 (dynamic)

General

Device Type:	3LCD projector - 720p
Built-in Devices:	Speaker
Networking:	Ethernet
Enclosure Colour:	Grey, white

Projector

Brightness (White):	3500 lumens
Brightness (Colour):	3500 lumens
Brightness (Reduced):	2900 lumens
Contrast Ratio:	300:1 / 14000:1 (dynamic)
Image Size:	152 cm - 254 cm
Projection Distance:	0.4 m - 0.6 m
Throw Ratio:	0.28:1
Digital Zoom Factor:	1.35x
Resolution:	WXGA - WXGA (1280 x 800)
Native Aspect Ratio:	16:10

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80%
Sound Emission:	35 dBA
Sound Emission (Economic Mode):	30 dBA

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years - carry-in
--------------------	---------------------------------------

Dimensions & Weight

Width:	36.7 cm
Depth:	40 cm
Height:	14.9 cm
Weight:	5.9 kg

Software / System Requirements

Software Included:	Epson Easy Interactive Tools, EasyMP Monitor, EasyMP Multi PC Projection
--------------------	--

Power

Power Source:	AC
Voltage Required:	AC 230V (50 - 60 Hz)

Projector

Colour Support: 1.07 billion colours

Bulb type: 250 Watt

Bulb life cycle: Up to 5000 hour(s) - normal mode | Up to 10000 hour(s) - economic mode

Features: sRGB colour profile, Blackboard Mode, EPSON 3LCD technology, Whiteboard Mode, Split Screen, Automatic Brightness Adjustment, Dynamic Lamp Control, Dynamic Mode, Theater Mode

Lens

Focus Type: Manual

Lens Aperture: F/1.6

Keystone Correction Direction: Horizontal, vertical

Vertical Keystone Correction: -3 / +3

Horizontal Keystone Correction: -3 / +3

Video Input

Analogue video Signal: RGB, composite video

Video Interfaces: VGA, HDMI, composite video, MHL

LAN and Wireless Image Transferring Protocols: Wired LAN

Speakers

Type: Integrated

Sound Output Mode: Mono

Output Power / Channel: 16 Watt

Speakers: 1 x mixed channel

Power

Power Consumption Operational: 354 Watt

Power Consumption Stand by: 0.39 Watt

Environmental Standards

TCO Certified: TCO Certified Projectors 8

Miscellaneous

Included Accessories: Wall mounting kit, pen tray, wireless remote control, interactive pens

Cables Included: 1 x USB cable

Mounting Kit: Included

Security Features: Security lock slot (cable lock sold separately), password protection

Expansion / Connectivity

Interfaces: 1 x component video / RGB input - 15 pin HD D-Sub (HD-15) | 1 x composite video input - RCA | 1 x Mobile High-Definition Link (MHL) / HDMI | 2 x HDMI input - 19 pin HDMI Type A | 1 x USB 2.0 - 4 pin USB Type A | 1 x USB 2.0 - 4 pin USB Type B | 3 x audio line-in - mini-phone stereo 3.5 mm | 1 x microphone | 1 x audio line-out - mini-phone stereo 3.5 mm | 1 x serial RS-232C - 9 pin D-Sub (DB-9) | 1 x network - RJ-45 | 1 x VGA input / output - 15 pin HD D-Sub (HD-15) | 1 x Sync in | 1 x Sync out