

Epson EB-770F - 3LCD projector - ultra short-throw - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white



In Stock(12)

SKU	V11HA79080
Product Description:	Epson EB-770F - 3LCD projector - ultra short-throw - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white
Device Type:	3LCD projector - 1080p
Colour:	White
Built-in Devices:	Speaker
Brightness (White):	4100 lumens
Brightness (Colour):	4100 lumens
Contrast Ratio:	2500000:1

General

Device Type:	3LCD projector - 1080p
Built-in Devices:	Speaker
Networking:	802.11a/b/g/n/ac, Ethernet
Enclosure Colour:	White

Projector

Brightness (White):	4100 lumens
Brightness (Colour):	4100 lumens
Brightness (Reduced):	2800 lumens
Contrast Ratio:	2500000:1
Image Size:	165.1 cm - 305 cm
Throw Ratio:	0.25 - 0.35:1
Digital Zoom Factor:	1.35x
Resolution:	Full HD

Environmental Parameters

Humidity Range Operating:	20 - 80%
Sound Emission:	37 dB
Sound Emission (Economic Mode):	27 dB

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years / 12000 hours - carry-in
--------------------	---

Dimensions & Weight

Width:	35.6 cm
Depth:	39.5 cm
Height:	13.3 cm
Weight:	5.9 kg

Software / System Requirements

Software Included:	EasyMP Multi PC Projection, Epson Projector Management Software, Epson Projector Content Manager
--------------------	--

Power

Power Source:	AC
---------------	----

Projector

Native Aspect Ratio: 16:9

Colour Support: 1.07 billion colours

Max Sync Rate (V x H): 240 Hz

Bulb type: Laser

Bulb life cycle: Up to 20000 hour(s) - normal mode | Up to 30000 hour(s) - economic mode

Features: Blackboard Mode, EPSON Quick Corner, Edge blending, EPSON 3LCD technology, Split Screen, Crestron RoomView, DICOM Simulation Mode, AMX Device Discovery, Direct Power On, Direct Power Off, Control4 Certified, Dynamic Mode, Digital Zoom, auto power on, Crestron Integrated Partner, document camera compatible, Presentation Mode, Extron IPLink certified, Cinema Mode, RGB liquid crystal shutter, 21:9 aspect ratio support

Lens

Type: Ultra short-throw lens

Focus Type: Manual

Lens Aperture: F/1.6

Keystone Correction Direction: Horizontal, vertical

Vertical Keystone Correction: -3 / +3

Horizontal Keystone Correction: -3 / +3

Video Input

Video Interfaces: VGA, HDMI, composite video

LAN and Wireless Image Transferring Protocols: IEEE 802.11b, IEEE 802.11g, wired LAN, IEEE 802.11a, IEEE 802.11n, Miracast, IEEE 802.11ac

Power

Voltage Required: AC 100-240 V (50 - 60 Hz)

Power Consumption Operational: 263 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Included Accessories: Remote control, battery for remote control

Security Features: Security lock slot (cable lock sold separately), password protection, control panel lock, Wireless LAN Lock, padlock, security cable hole

Security Slot Type: Kensington security slot

Compliant Standards: IPv6, IPv4

Expansion / Connectivity

Interfaces: 2 x VGA input - 15 pin HD D-Sub (HD-15) ; 3 x HDMI input - 19 pin HDMI Type A ; 2 x USB 2.0 - 4 pin USB Type A ; 1 x composite video input ; 3 x audio line-in - mini-phone stereo 3.5 mm ; 1 x audio line-out - mini-phone stereo 3.5 mm ; 1 x USB 2.0 - 4 pin USB Type B ; 1 x serial RS-232C ; 1 x network - RJ-45 ; 1 x VGA output - 15 pin HD D-Sub (HD-15)

Speakers

Type: Integrated

Sound Output Mode: Mono

Output Power / Channel: 16 Watt

Speakers: 1 x mixed channel