

Epson EB-800F - 3LCD projector - ultra short-throw - LAN - white



SKU	V11H923540
Product Description:	Epson EB-800F - 3LCD projector - ultra short-throw - LAN - white
Device Type:	3LCD projector - 1080p
Colour:	White
Built-in Devices:	Stereo speakers
Brightness (White):	5000 lumens
Brightness (Colour):	5000 lumens
Contrast Ratio:	2500000:1 (dynamic)

General

Device Type:	3LCD projector - 1080p
Built-in Devices:	Stereo speakers
Networking:	Ethernet
Enclosure Colour:	White

Environmental Parameters

Min Operating Temperature:	-10 °C
Max Operating Temperature:	60 °C
Humidity Range Operating:	20 - 80%
Sound Emission:	36 dB
Sound Emission (Economic Mode):	27 dB

Projector

Brightness (White):	5000 lumens
Brightness (Colour):	5000 lumens
Brightness (Reduced):	3500 lumens
Contrast Ratio:	2500000:1 (dynamic)
Image Size:	165.1 cm - 330 cm
Projection Distance:	0.4 m
Throw Ratio:	0.27 - 0.37:1
Digital Zoom Factor:	1.35x
Resolution:	Full HD - Full HD (1920 x 1080)

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years / 12000 hours
--------------------	--

Dimensions & Weight

Width:	45.8 cm
Depth:	21 cm
Height:	37.5 cm
Weight:	9.4 kg

Software / System Requirements

Software Included:	Epson iProjection, Epson Projector Content Manager
--------------------	--

Power

Power Source:	AC
---------------	----

Projector

Native Aspect Ratio: 16:9

Colour Support: 1.07 billion colours

Max Sync Rate (V x H): 240 Hz

Bulb type: Laser diode

Bulb life cycle: Up to 20000 hour(s) - normal mode | Up to 30000 hour(s) - economic mode

Features: sRGB colour profile, freeze frame, Blackboard Mode, Edge blending, EPSON 3LCD technology, Split Screen, DICOM Simulation Mode, Direct Power On, Direct Power Off, Dynamic Mode, auto power on, Auto Calibration, Eco Mode, instant on/off, Presentation Mode, Cinema Mode

Lens

Type: Ultra short-throw lens

Focus Type: Manual

Lens Aperture: F/1.5

Keystone Correction Direction: Horizontal, vertical

Vertical Keystone Correction: -3 / +3

Horizontal Keystone Correction: -3 / +3

Video Input

Video Interfaces: VGA, HDMI, composite video, HDBaseT

LAN and Wireless Image Transferring Protocols: Wired LAN

Power

Voltage Required: AC 120/230 V (50 - 60 Hz)

Power Consumption Operational: 366 Watt

Power Consumption Stand by: 0.5 Watt

Environmental Standards

TCO Certified: TCO Certified Projectors 8

Miscellaneous

Included Accessories: Lens cover, cable cover, remote control, battery for remote control

Security Features: Security lock slot (cable lock sold separately), password protection, padlock

Security Slot Type: Kensington security slot

Expansion / Connectivity

Interfaces: 2 x VGA input - 15 pin HD D-Sub (HD-15) | 1 x HDMI output - 19 pin HDMI Type A | 3 x HDMI input - 19 pin HDMI Type A | 2 x USB 2.0 - 4 pin USB Type A | 1 x HDBaseT - RJ-45 | 3 x audio line-in - mini-phone stereo 3.5 mm | 1 x audio line-out - mini-phone stereo 3.5 mm | 1 x USB 2.0 - 4 pin USB Type B | 1 x serial RS-232C | 1 x network - RJ-45 | 1 x VGA output - 15 pin HD D-Sub (HD-15)

Speakers

Type: Integrated

Sound Output Mode: Stereo

Output Power / Channel: 8 Watt

Speakers: 2 x right / left channel