

Epson EB-992F - 3LCD projector - 802.11n wireless / LAN / Miracast - white



In Stock(14)

SKU	V11H988040
Product Description:	Epson EB-992F - 3LCD projector - 802.11n wireless / LAN / Miracast - white
Device Type:	3LCD projector - 1080p
Colour:	White
Built-in Devices:	Speaker
Brightness (White):	4000 lumens
Brightness (Colour):	4000 lumens
Contrast Ratio:	16000:1 (dynamic)

General

Device Type:	3LCD projector - 1080p
Built-in Devices:	Speaker
Networking:	802.11b/g/n, Ethernet
Enclosure Colour:	White

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80%
Sound Emission:	37 dBA
Sound Emission (Economic Mode):	28 dBA

Projector

Brightness (White):	4000 lumens
Brightness (Colour):	4000 lumens
Brightness (Reduced):	2400 lumens
Contrast Ratio:	16000:1 (dynamic)
Image Size:	76 cm - 762 cm
Projection Distance:	1.76 m - 2.86 m
Throw Ratio:	1.32 - 2.14:1
Resolution:	Full HD - Full HD (1920 x 1080)

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years - carry-in ! Limited warranty - lamp - 5 years / 1000 hours
--------------------	---

Dimensions & Weight

Width:	30.9 cm
Depth:	28.2 cm
Height:	9 cm
Weight:	3.1 kg

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50 - 60 Hz)

Projector

Native Aspect Ratio:	16:9
----------------------	------

Colour Support:	1.07 billion colours
-----------------	----------------------

Max Sync Rate (V x H):	120 Hz
------------------------	--------

Bulb type:	UHE 230 Watt
------------	--------------

Bulb life cycle:	Up to 6500 hour(s) - normal mode Up to 17000 hour(s) - economic mode
------------------	--

Features:	Blackboard Mode, EPSON Quick Corner, Crystal Clear Fine (C2 Fine), Split Screen, PJLink, Direct Power On, Direct Power Off, Control4 Certified, Dynamic Mode, USB Display, Extron Control System, AMX Control System, document camera compatible, Presentation Mode, Cinema Mode, RGB liquid crystal shutter
-----------	--

Lens

Focus Type:	Manual
-------------	--------

Lens Aperture:	F/1.51-1.99
----------------	-------------

Zoom Type:	Manual
------------	--------

Zoom Factor:	1.6x
--------------	------

Keystone Correction Direction:	Horizontal, vertical
--------------------------------	----------------------

Vertical Keystone Correction:	-30 / +30
-------------------------------	-----------

Horizontal Keystone Correction:	-30 / +30
---------------------------------	-----------

Video Input

Video Interfaces:	VGA, HDMI, composite video
-------------------	----------------------------

LAN and Wireless Image Transferring Protocols:	IEEE 802.11b, IEEE 802.11g, wired LAN, IEEE 802.11n, Miracast
--	---

Power

Power Consumption Operational:	327 Watt
--------------------------------	----------

Miscellaneous

Included Accessories:	Wireless remote control, wireless LAN unit, battery for remote control
-----------------------	--

Cables Included:	1 x VGA cable
------------------	---------------

Security Features:	Security lock slot (cable lock sold separately), password protection, control panel lock, security cable hole
--------------------	---

Security Slot Type:	Kensington security slot
---------------------	--------------------------

Expansion / Connectivity

Interfaces:	2 x VGA input - 15 pin HD D-Sub (HD-15) 1 x VGA output - 15 pin HD D-Sub (HD-15) 2 x HDMI input - 19 pin HDMI Type A 1 x USB 2.0 - 4 pin USB Type A 1 x USB 2.0 - 4 pin USB Type B 2 x audio line-in - mini-phone stereo 3.5 mm 1 x audio line-out - mini-phone stereo 3.5 mm 1 x serial RS-232C - 9 pin D-Sub (DB-9) 1 x network - RJ-45 1 x microphone 1 x composite video input - RCA
-------------	--

Speakers

Type:	Integrated
-------	------------

Sound Output Mode:	Mono
--------------------	------

Output Power / Channel:	16 Watt
-------------------------	---------

Speakers:	1 x mixed channel
-----------	-------------------