

Epson EB-L265F - 3LCD projector - 802.11a/b/g/n/ac wireless / LAN/ Miracast - black



In Stock(3)

SKU	V11HA72180
Product Description:	Epson EB-L265F - 3LCD projector - 802.11a/b/g/n/ac wireless / LAN/ Miracast - black
Device Type:	3LCD projector - 1080p
Colour:	Black
Built-in Devices:	Speaker
Brightness (White):	4600 lumens
Brightness (Colour):	4600 lumens
Contrast Ratio:	2500000:1 (dynamic)

General

Device Type:	3LCD projector - 1080p
Built-in Devices:	Speaker
Networking:	802.11a/b/g/n/ac, Ethernet
Enclosure Colour:	Black

Projector

Brightness (White):	4600 lumens
Brightness (Colour):	4600 lumens
Brightness (Reduced):	3200 lumens
Contrast Ratio:	2500000:1 (dynamic)
Image Size:	78.7 cm - 787 cm
Throw Ratio:	1.32 - 2.12:1
Resolution:	Full HD
Native Aspect Ratio:	16:9

Environmental Parameters

Humidity Range Operating:	20 - 80%
Sound Emission:	37 dB
Sound Emission (Economic Mode):	27 dB

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years / 12000 hours - carry-in
--------------------	---

Dimensions & Weight

Weight:	4.2 kg
---------	--------

Software / System Requirements

Software Included:	EasyMP Multi PC Projection, Epson Projector Content Manager, Epson Projector Management Software
--------------------	--

Power

Power Source:	AC
Voltage Required:	AC 220-240 V (50 - 60 Hz)

Projector

Colour Support: 1.07 billion colours

Max Sync Rate (V x H): 240 Hz

Bulb type: Laser

Bulb life cycle: Up to 20000 hour(s) - normal mode | Up to 30000 hour(s) - economic mode

Features: EPSON 3LCD technology, RGB liquid crystal shutter, arc correction, auto power on, Direct Power Off, Direct Power On, document camera compatible, Edge blending, EPSON Quick Corner, screen mirroring, Split Screen, Super Resolution, web control, web remote, 16:6 aspect ratio support, Crestron Integrated Partner, Crestron RoomView, Extron IPLink certified, AMX Device Discovery, Control4 SDDP, Blackboard Mode, Cinema Mode, Dynamic Mode, Presentation Mode, Vivid Mode

Lens

Focus Type: Manual

Lens Aperture: F/1.51-1.77

Zoom Type: Manual

Zoom Factor: 1.62x

Keystone Correction Direction: Horizontal, vertical

Vertical Keystone Correction: -30 / +30

Horizontal Keystone Correction: -30 / +30

Video Input

Video Interfaces: VGA, HDMI, composite video

LAN and Wireless Image Transferring Protocols: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, wired LAN, Miracast

Power

Power Consumption Operational: 260 Watt

Power Consumption Standby: 0.5 Watt

Miscellaneous

Included Accessories: Remote control, battery for remote control, cable cover

Security Features: Security lock slot (cable lock sold separately), security bar, control panel lock, padlock, security cable hole, Wireless LAN Lock, Wireless LAN security, password protection

Security Slot Type: Kensington security slot

Compliant Standards: HDCP 2.3, IPv6

Expansion / Connectivity

Interfaces: 1 x USB 2.0 - 4 pin USB Type A | 1 x USB 2.0 - 4 pin USB Type B | 2 x VGA input - 15 pin HD D-Sub (HD-15) | 1 x VGA output | 2 x HDMI | 1 x composite video input - RCA | 1 x network - RJ-45 | 1 x audio line-out - mini-phone stereo 3.5 mm | 2 x audio line-in - mini-phone stereo 3.5 mm | 1 x serial RS-232C

Speakers

Type: Integrated

Sound Output Mode: Mono

Output Power / Channel: 16 Watt

Speakers: 1 x mixed channel