

Epson EB-L635SU - 3LCD projector - 802.11a/b/g/n/ac wireless / LAN/ Miracast - black



07-05-2024

SKU	V11HA29140
Product Description:	Epson EB-L635SU - 3LCD projector - 802.11a/b/g/n/ac wireless / LAN/ Miracast - black
Device Type:	3LCD projector - 1080p
Colour:	Black
Built-in Devices:	0.67-inch LCD
Brightness (White):	6000 lumens
Brightness (Colour):	6000 lumens
Contrast Ratio:	2500000:1 (dynamic)

General

Device Type:	3LCD projector - 1080p
Built-in Devices:	0.67-inch LCD
Networking:	802.11a/b/g/n/ac, Ethernet
Enclosure Colour:	Black

Projector

Brightness (White):	6000 lumens
Brightness (Colour):	6000 lumens
Brightness (Reduced):	4200 lumens
Contrast Ratio:	2500000:1 (dynamic)
Image Size:	127 cm - 508 cm
Projection Distance:	0.9 m - 3.5 m
Throw Ratio:	0.8 - 1.07:1
Digital Zoom Factor:	1.35x

Environmental Parameters

Humidity Range Operating:	20 - 80%
Sound Emission:	38 dBA
Sound Emission (Economic Mode):	27 dBA

Dimensions & Weight (Shipping)

Shipping Width:	53.1 cm
Shipping Depth:	56.4 cm
Shipping Height:	20.3 cm
Shipping Weight:	11.79 kg

Dimensions & Weight

Width:	44 cm
Depth:	33.4 cm
Height:	13.6 cm
Weight:	8.4 kg

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50 - 60 Hz)

Projector

Resolution: WUXGA - WUXGA (1920 x 1200)

Native Aspect Ratio: 16:10

Colour Support: 1.07 billion colours

Bulb type: Laser

Bulb life cycle: Up to 20000 hour(s) - normal mode | Up to 30000 hour(s) - economic mode

Features: EPSON Quick Corner, Edge blending, EPSON 3LCD technology, Web Remote Control, DICOM Simulation Mode, Direct Power On, Direct Power Off, Dynamic Mode, full 10-bit image processing, auto power on, document camera compatible, Cinema Mode

Lens

Focus Type: Manual

Lens Aperture: F/1.7

Keystone Correction Direction: Horizontal, vertical

Vertical Keystone Correction: -30 / +30

Horizontal Keystone Correction: -30 / +30

Lens Shift Type: Manual

Lens Shift Direction: Horizontal, vertical

Vertical Lens Shift: 50% / 50%

Horizontal Lens Shift: 20% / 20%

Video Input

Video Interfaces: VGA, HDMI

LAN and Wireless Image Transferring Protocols: IEEE 802.11b, IEEE 802.11g, wired LAN, IEEE 802.11a, IEEE 802.11n, Miracast, IEEE 802.11ac

Power

Power Consumption Operational: 345 Watt

Power Consumption Stand by: 0.3 Watt

Miscellaneous

Included Accessories: Cable cover, remote control, battery for remote control

Security Features: Security lock slot (cable lock sold separately), password protection, control panel lock, Wireless LAN Lock, security cable hole

Security Slot Type: Kensington security slot

Expansion / Connectivity

Interfaces: 2 x USB 2.0 - 4 pin USB Type A | 1 x USB 2.0 - 4 pin USB Type B (management) | 1 x serial RS-232C | 1 x network - RJ-45 | 2 x VGA input - 15 pin HD D-Sub (HD-15) | 1 x VGA output - 15 pin HD D-Sub (HD-15) | 2 x HDMI - 19 pin HDMI Type A | 1 x HDBaseT - RJ-45 | 1 x audio line-out - mini-phone stereo 3.5 mm | 2 x audio line-in - mini-phone stereo 3.5 mm | 1 x HDMI output - 19 pin HDMI Type A

Speakers

Type: Integrated

Sound Output Mode: Mono

Output Power / Channel: 10 Watt

Speakers: 1 x mixed channel