

Epson EB-PU2010B - 3LCD projector - LAN - black



In Stock(3)

SKU	V11HA52840
Product Description:	Epson EB-PU2010B - 3LCD projector - LAN - black
Device Type:	3LCD projector - 1080p
Colour:	Black
Built-in Devices:	1.03-inch LCD
Brightness (White):	10000 lumens
Brightness (Colour):	10000 lumens
Contrast Ratio:	2000:1 / 2500000:1 (dynamic)

General

Device Type:	3LCD projector - 1080p
Built-in Devices:	1.03-inch LCD
Networking:	Ethernet
Enclosure Colour:	Black

Projector

Brightness (White):	10000 lumens
Brightness (Colour):	10000 lumens
Brightness (Reduced):	7000 lumens
Contrast Ratio:	2000:1 / 2500000:1 (dynamic)
Throw Ratio:	0.35 - 7.41:1
Resolution:	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio:	16:10
Colour Support:	1.07 billion colours
Bulb type:	Laser
Bulb life cycle:	Up to 20000 hour(s) - normal mode ; Up to 30000 hour(s) - economic mode

Environmental Parameters

Humidity Range Operating:	20 - 80%
Sound Emission:	37 dBA
Sound Emission (Economic Mode):	30 dBA

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years - carry-in
--------------------	---------------------------------------

Dimensions & Weight

Width:	54.5 cm
Depth:	43.6 cm
Height:	18.9 cm
Weight:	16.8 kg

Software / System Requirements

Software Included:	Epson Projector Management Software, Epson iProjection, Epson Projector Content Manager, Epson Projector Professional Tool
--------------------	--

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational:	535 Watt

Projector

Features:	EPSON Quick Corner, Edge blending, EPSON 3LCD technology, PJLink, Web Remote Control, DICOM Simulation Mode, AMX Device Discovery, Direct Power On, Direct Power Off, Dynamic Mode, full 10-bit image processing, auto power on, SNMP support, Extron XTP certified, 4K Enhancement, Presentation Mode, Extron IPLink certified, Cinema Mode, RGB liquid crystal shutter

Lens

Keystone Correction Direction:	Horizontal, vertical
Vertical Keystone Correction:	-45 / +45
Horizontal Keystone Correction:	-30 / +30

Video Input

Video Interfaces:	VGA, HDMI, DVI, 3G-SDI, HDBaseT
LAN and Wireless Image Transferring Protocols:	Wired LAN

Power

Power Consumption Stand by:	0.5 Watt
-----------------------------	----------

Miscellaneous

Included Accessories:	Cable cover, remote control, battery for remote control
Security Features:	Security lock slot (cable lock sold separately), password protection, control panel lock, Wireless LAN Lock, padlock, security cable hole
Security Slot Type:	Kensington security slot
Compliant Standards:	ISO/IEC 21118:2012, HDCP 2.3, IPv6

Expansion / Connectivity

Interfaces:	2 x USB 2.0 - 4 pin USB Type A 1 x USB 2.0 - 4 pin USB Type B (management) 1 x serial RS-232C 1 x network - RJ-45 1 x VGA input - 15 pin HD D-Sub (HD-15) 1 x DVI input 1 x HDBaseT - RJ-45 1 x audio line-out - mini-phone stereo 3.5 mm HDMI - 19 pin HDMI Type A 3G-SDI input 3G-SDI output
-------------	--

