

Fujitsu P24-8 WE Neo - LED monitor - 24"



Not in stock

SKU	S26361-K1647-V140
Product Description:	Fujitsu P24-8 WE Neo - LED monitor - 24"
Device Type:	LED-backlit LCD monitor - 24"
Energy Class:	Class E
Energy Consumption per Year:	28 kWh
Power Consumption (On mode):	17.9 W
Daisy Chaining:	Yes
Features:	Presence sensor, USB 3.1 Gen 1 hub

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class E
Energy Consumption per Year:	28 kWh
Diagonal Size:	24"
Daisy Chaining:	Yes
Built-in Devices:	Presence sensor, USB 3.1 Gen 1 hub
Panel Type:	IPS
Aspect Ratio:	16:10
Native Resolution:	WUXGA 1920 x 1200
Pixel Pitch:	0.27 mm
Brightness:	300 cd/m²
Contrast Ratio:	1000:1 / 20000000:1 (dynamic)
Colour Support:	16.7 million colours
Colour Gamut:	100% sRGB, 77% NTSC
Response Time:	5 ms (grey-to-grey)

Compatibility Information

Designed For:	Fujitsu Celsius J550/2-L, J580, M770powerx, M770x, R970B, R970Bpower, W580power+ ; Fujitsu ESPRIMO D538/E94+, D958/E85+, P558, Q958/MRE
---------------	---

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	10 - 85% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years - pick-up and return
--------------------	---

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 53.18 cm - depth: 21.27 cm - height: 36.77 cm - weight: 5.82 kg ; Without stand - width: 53.18 cm - depth: 5.6 cm - height: 35 cm - weight: 3.8 kg
------------------------------	--

General

Vertical Refresh Rate:	48 - 76 Hz
Horizontal Refresh Rate:	30 - 82 kHz
Horizontal Viewing Angle:	178
Vertical Viewing Angle:	178
Screen Coating:	Anti-glare, 3H Hard Coating
Backlight Technology:	LED backlight
Colour Temperature:	5000K, 6500K, 7500K
OSD Languages:	Danish, Czech, Chinese (traditional), Chinese (simplified), English, German, French, Italian, Norwegian, Portuguese, Polish, Finnish, Swedish, Russian, Spanish, Dutch, Turkish, Arabic, Japanese
Features:	HDCP, Overdrive technology, touch keys, Auto Brightness Control, ECO button, DisplayView, DICOM calibrated, Low Blue Light Mode, AutoPivot sensor, Workplace Lighting Guide, 24/7 operating mode, Narrow Border Display
Colour:	Marble grey
Dimensions (WxDxH):	53.18 cm x 21.27 cm x 36.77 cm - with stand
Weight:	5.82 kg

Audio

Type:	Speakers - stereo
Output Power / Channel:	2 Watt

Connectivity

Interfaces:	DisplayPort DisplayPort output HDMI DVI-D Audio line-out 4 x USB 3.1 Gen 1 downstream USB 3.1 Gen 1 upstream
-------------	--

Software / System Requirements

Included Software:	Display View IT Suite
--------------------	-----------------------

Power

Input Voltage:	AC 120/230 V (50/60 Hz)
Power Consumption (On mode):	17.9 W
Power Consumption SDR (On mode):	17.9 kWh/1000h
Power Consumption (Typical):	14.4 Watt
Power Consumption Stand by:	0.3 Watt
Power Consumption Sleep:	0.2 Watt

Miscellaneous

Features:	Security lock slot (cable lock sold separately), cable guide, "Always On" USB port
Cables Included:	1 x DisplayPort cable - 1.8 m 1 x USB cable - USB Type A to B - 1.8 m
Compliant Standards:	FCC Class B certified, TUV GS, VCCI, cUL, EN 60950, SASO, DDC/CI, RoHS, WEEE, S Mark, Directive 2004/108/EEC, EAC, RCM, VESA MIS-D 100 C, TUV Rheinland Low Blue Light Certification, TUV Rheinland Flicker Free Certification, ISO 9241-307 Class 1
Localisation:	Europe
Security Slot Type:	Kensington security slot

Mechanical

Display Position Adjustments:	Height, pivot (rotation), swivel, tilt
Tilt Angle:	-5/+35
Swivel Angle:	345
Rotation Angle:	90
Height Adjustment:	130 mm
VESA Mounting Interface:	100 x 100 mm