

Fujitsu PR09 - port replicator - USB-C - 2 x DP - 1GbE



Not in stock

SKU	S26391-F6007-L500
Product Description:	Fujitsu PR09 - port replicator - USB-C - 2 x DP - 1GbE
Product Type:	Port replicator
Docking Interface:	USB-C
Video Interfaces:	2 x DP
Dimensions (WxDxH):	20 cm x 9.76 cm x 2.9 cm
Weight:	340 g
Colour:	Black

General

Product Type:	Port replicator
Width:	20 cm
Depth:	9.76 cm
Height:	2.9 cm
Weight:	340 g
Enclosure Colour:	Black
Localisation:	Europe

Networking

Data Link Protocol:	Gigabit Ethernet
---------------------	------------------

Expansion / Connectivity

Interfaces:	1 x network - Ethernet 1000 - RJ-45 1 x USB-C with Power Delivery - 24 pin USB-C 1 x USB 3.1 Gen 2 with Battery Charging 1.2 - 24 pin USB-C 2 x USB 3.1 Gen 2 - 24 pin USB-C 4 x USB 3.1 Gen 1 - 9 pin USB Type A 2 x display / video - DisplayPort - 20 pin DisplayPort 1 x audio - SPDIF
-------------	--

Miscellaneous

Cables Included:	1 x USB-C cable - external - 1 m
Features:	Security lock slot (cable lock sold separately), Preboot Execution Environment (PXE) support, 4 LED indicators

Compatibility Information

Designed For:	Fujitsu Celsius H7510, J550, J550/2, J550/2-L, J580, M730, M730 POWER, M740, M740 POWER Fujitsu ESPRIMO C720, C910-L, D538/E94+, D556/2/E85+, D556/2/E90+, D556/E85+, D556/E90+, D556/MX, D556/PX, D738/E94+, D756, D756/E85+, D756/E90+, D756/E94+, D757/E85+, D757/E90+, D757/E94+, D956/E85+, D956/E90+, D956/E94+, D956/LL, D956/M (International Energy Star Program), D957/E85+, D957/E90+, D957/E94+, D958/E85+, D958/E94+, E420 D, E420 E85+, E520 E85+, E720 E85+, E720 E90+, E920 0-Watt, E920 E85+, E920 E90+, G6012, G9010, G9012, P420 E85+, P520 E85+, P558, P720 E85+, P720 E90+, P920, P920 0-Watt, P920 E85+, P920 E90+, P956 E90+, PH320 E85+, Q520, Q520/K, Q920, Q958/MRE Fujitsu FUTRO X913-T, X923 Fujitsu LIFEBOOK A514, A555, A555G, E459, E5410, E544, E549, E5510, E559, E734, E734/K, E744, E754, P702, P702 Security Selection, P727, S935, S935/K, S935/KX, T725, T935, T935.biling, U729, U7310, U7410, U745, U749, U7510, U759, U904, U9310, U9310x Fujitsu Stylistic R726, R727, V535 Industrial
---------------	--

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C

Manufacturer Warranty

Miscellaneous

Compliant Standards: FCC Class B certified, UL, VCCI, BSMI, cUL, SASO, ICES-003 Class B, CCC, PSE Mark, JEITA, S Mark, cTUVus, KC, DisplayLink Plug and Display, EAC, RCM, DisplayPort 1.2a

Manufacturer Warranty

Service & Support: Limited warranty - 3 years - carry-in

Power

Power Device:	Power adapter
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Provided:	120 Watt

System Requirements

OS Required: Microsoft Windows

