

Capture Swordfish - POS In a Box - all-in-one - Celeron J1900 2 GHz - 8 GB - SSD 128 GB - LCD 15" - with cash drawer 410mm 4B/8C



Not in stock

SKU	CA-PIB-1
Product Description:	Capture Swordfish - POS In a Box - all-in-one - Celeron J1900 2 GHz - 8 GB - SSD 128 GB - LCD 15" - with cash drawer 410mm 4B/8C
Type:	Point of sale terminal - all-in-one
Processor:	1 x Intel Celeron J1900 / 2 GHz (, up to 2.42 GHz, (Quad-Core)
Cache Memory:	2 MB
Cache Per Processor:	2 MB
RAM:	8 GB DDR3L SDRAM
Hard Drive:	SSD 128 GB

General

Type:	Point of sale terminal
Product Form Factor:	All-in-one
Built-in Devices:	Speaker, capacitive touch screen
Colour:	Black
Bundled with:	Cash drawer 410mm 4B/8C

Processor / Chipset

CPU:	Intel Celeron J1900
Clock Speed:	2 GHz
Max Turbo Speed:	2.42 GHz
Number of Cores:	Quad-Core
CPU Qty:	1
Max CPU Qty:	1

Cache Memory

Installed Size:	2 MB
Cache Per Processor:	2 MB

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Dimensions & Weight

Dimensions & Weight Details:	13.2 cm - 18.2 cm - 12.5 cm - 1.3 kg - printer 41 cm - 41.5 cm - 10 cm - 6.8 kg - cash drawer
Width:	35.5 cm
Depth:	20.5 cm
Height:	30.3 cm
Weight:	5 kg

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Operating System / Software

OS Provided:	Windows 10 IoT 64-bit Edition
--------------	-------------------------------

RAM

Installed Size:	8 GB
Technology:	DDR3L SDRAM
Effective Memory Speed:	1333 MHz
Form Factor:	SO-DIMM 204-pin

Hard Drive

Type:	SSD
Capacity:	1 x 128 GB

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	LCD
Touchscreen:	Yes
Diagonal Size:	15"
Native Resolution:	1024 x 768 (XGA)
Widescreen Display:	No
Image Aspect Ratio:	4:3
Image Brightness:	300 cd/m²
Monitor Features:	Projected Capacitive Touch (P-CAP) technology, tilt stand (15°- 85°)

Graphics Controller

Graphics Processor:	Intel HD Graphics
Video Interfaces:	VGA

Power

Device Type:	Power adapter
Voltage Required:	AC 120/230 V (50/60 Hz)

Miscellaneous

VESA Mounting Interface:	75 x 75 mm
Compliant Standards:	VESA FDMI, FCC, RoHS, WEEE

Expansion / Connectivity

Slots:	1 mSATA
Interfaces:	1 x LAN (Gigabit Ethernet) - RJ-45 ; 5 x USB 2.0 (4 bottom, 1 side) ; 1 x VGA ; 4 x serial - DB-9 (powered (DC 5V/12V selectable)) ; 1 x parallel - DB-25 ; 1 x cash drawer - RJ-11 (powered (DC 12V/24V)) ; 2 x serial (2 internal)

Printer

Type:	Receipt printer
Technology:	Direct thermal
Interface:	Serial, USB, Ethernet
Max Print Speed:	220 mm/sec
Media Size:	Roll (8 cm)

Networking

Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
---------------------	---