

HPE Modular Smart Array 2060 16Gb Fibre Channel SFF Storage - hard drive array - TAA Compliant



20-05-2024

SKU	R9G38B
Product Description:	HPE Modular Smart Array 2060 16Gb Fibre Channel SFF Storage - hard drive array - TAA Compliant
Device Type:	Hard drive array
Enclosure Type:	Rack-mountable - 2U
Total Array Capacity:	0 TB
Max Supported Capacity:	921.6 TB
Interface:	16Gb Fibre Channel
Maximum LUNs:	512

General

Device Type:	Hard drive array
Enclosure Type:	Rack-mountable - 2U

Manufacturer Warranty

Service & Support:	Limited warranty - parts - 3 years
--------------------	------------------------------------

Chassis

Installed Devices / Modules Qty:	0
Supported Devices / Modules Qty:	24
Supported Drives:	SAS-3

Power

Power Device:	2 x internal power supply - hot-plug
Max Supported Qty:	2
Power Redundancy:	Yes
Power Redundancy Scheme:	1+1
Power Provided:	764 Watt

Storage

Total Array Capacity:	0 TB
Max Supported Capacity:	921.6 TB
HDD Array External Interface:	16Gb Fibre Channel
Maximum LUNs:	512

Environmental Standards

ENERGY STAR Certified:	Yes
------------------------	-----

Processor

CPU:	No CPU
------	--------

Miscellaneous

Features:	SNMP support, SMTP support
TAA Compliant:	Yes
Included Accessories:	Rack mounting kit

Storage Controller

Type:	RAID (SAS-3)
Installed Qty:	2

System Requirements

Storage Controller

Interface Type:	SAS 12Gb/s
Data Transfer Rate:	1.2 GBps
Cache / Buffer Size (Max):	24 GB
Max Storage Devices Qty:	240
RAID Level:	RAID 0, RAID 1, RAID 3, RAID 5, RAID 6, RAID 10, RAID 50

Storage Controller (2nd)

Installed Qty:	2
----------------	---

Hard Drive

Type:	No HDD
-------	--------

System Requirements

OS Required:	HP-UX, SuSe Linux, Apple MacOS X, Microsoft Windows, Red Hat Enterprise Linux, HP OpenVMS, Microsoft Windows Server 2012, VMware ESXi 5.x, Microsoft Windows Server 2012 R2, Microsoft Windows Server 2012 R2 with Hyper-V, VMware ESXi 6.x
--------------	---

Expansion / Connectivity

Expansion Bays:	24 (total) / 24 (free) - 2.5" SFF
Interfaces:	8 x SAS 12Gb/s ; 2 x mini-USB 2.0 (management) ; 2 x Ethernet 1000Base-T (management) - RJ-45

