

HPE - power supply - hot-plug / redundant - 1600 Watt - 1736 VA



SKU	830272-B21
Product Description:	HPE - power supply - hot-plug / redundant - 1600 Watt - 1736 VA
Device Type:	Power supply - hot-plug / redundant - plug-in module
Specification Compliance:	Flex Slot
80 PLUS Certification:	80 PLUS Platinum
Weight:	910 g
Input Voltage:	AC 200-240 V
Power Capacity:	1600 Watt / 1736 VA

General

Device Type:	Power supply - hot-plug / redundant - plug-in module
Specification Compliance:	Flex Slot

Compatibility Information

Power Device

Input Voltage:	AC 200-240 V
Frequency Required:	50 - 60 Hz
Input Connectors:	Power IEC 60320 C14
Power Capacity:	1600 Watt / 1736 VA
Efficiency:	94%
80 PLUS Certification:	80 PLUS Platinum

Miscellaneous

Compliant Standards:	UL, TUV, C-Tick, BSMI, cUL, CCC, KCC, WEEE, low halogen, CISPR Class A
----------------------	--

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	55 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Dimensions & Weight

Width:	6.8 cm
Depth:	22.53 cm
Height:	4.04 cm
Weight:	910 g

Dimensions & Weight (Shipping)

Shipping Width:	19.05 cm
Shipping Depth:	37.47 cm
Shipping Height:	14.61 cm
Shipping Weight:	1.59 kg

Compatibility Information

	HPE Apollo 4200 Gen10 192TB Qumulo Hybrid Node (1600 Watt), 4200 Gen10 336TB Archive Node with 25Gb NIC for Qumulo (1600 Watt), 4200 Gen10 384TB 25Gb Capacity Server for Cohesity DataPlatform (1600 Watt), 4200 Gen10 384TB Capacity Server for Cohesity DataPlatform (1600 Watt), 4200 Gen10 for HPE Ezmeral Container Platform (1600 Watt), 4200 Gen10 for HPE Ezmeral Tracking (1600 Watt), 4200 Gen10 Qumulo Archive Node (1600 Watt), 4200 Gen10 Qumulo Hybrid Node (1600 Watt), n2600 Gen10 Plus Small Form Factor (1600 Watt) ; HPE Nimble Storage dHCI Large Solution with HPE ProLiant DL380 Gen10 (1600 Watt), Medium Solution with HPE ProLiant DL325 Gen10 Plus (1600 Watt), Medium Solution with HPE ProLiant DL360 Gen10 (1600 Watt), Small Solution with HPE ProLiant DL360 Gen10 (1600 Watt) ; HPE ProLiant DL180 Gen10 Entry (1600 Watt), DL325 Gen10 Plus All-NVMe Flash Node for Qumulo (1600 Watt), DL325 Gen10 Plus All-NVMe Flash Node for Software Defined Storage (1600 Watt), DL325 Gen10 Plus for Weka BAsE Tracking (1600 Watt), DL325 Gen10 Plus for Weka Expansion Tracking (1600 Watt), DL325 Gen10 Solution (1600 Watt), DL360 Gen10 All Flash Server for Weka (1600 Watt), DL360 Gen10 Compute Server for Cohesity DataPlatform (1600 Watt), DL360 Gen10 Performance for Cohesity DataPlatform (1600 Watt), DL360 Gen10 Remote Office Branch Office Server for Cohesity DataPlatform (1600 Watt), DL380 Gen10 All Flash Server for Datera (1600 Watt), DL380 Gen10 for SAP HANA Compute Block (1600 Watt), DL380 Gen10 Hybrid Server for Datera (1600 Watt), DL380 Gen10 Network Choice for CTERA (1600 Watt), DL380 Gen10 Server for CTERA (1600 Watt), DL380 Gen10 SMB Networking Choice (1600 Watt), DL385 Gen10 SMB (1600 Watt), DL560 Gen10 for SAP HANA Compute Block (1600 Watt), DX385 Gen10 Plus (1600 Watt), ML350 Gen10 SMB (1600 Watt), XL290n Gen10 Plus (1600 Watt) ; HPE SimpliVity 380 Gen10 Network Choice G Node (1600 Watt), 380 Gen10 Network Choice H Node (1600 Watt)
Designed For:	

