


HPE ProLiant MicroServer Gen11 - rack-mountable Pentium Gold G7400 3.7 GHz - 16 GB - HDD 1 TB



22-11-2024

SKU	P74439-425
Product Description:	HPE ProLiant MicroServer Gen11 - rack-mountable Pentium Gold G7400 3.7 GHz - 16 GB - HDD 1 TB
Type:	Server - rack-mountable
Server Scalability:	1-way
Processor:	1 x Intel Pentium Gold G7400 / 3.7 GHz (Dual-Core)
Processor Main Features:	Intel Turbo Boost Technology
Cache Memory:	6 MB
Cache Per Processor:	6 MB

General

Type:	Server
Product Form Factor:	Rack-mountable
Embedded Security:	Trusted Platform Module (TPM 1.2) Security Chip
Server Scalability:	1-way
Internal Bays Qty:	4
Front Accessible Bays Qty:	1

Processor / Chipset

CPU:	Intel Pentium Gold G7400
Clock Speed:	3.7 GHz
Number of Cores:	Dual-Core
CPU Qty:	1
Max CPU Qty:	1
L2 cache:	2.5 MB
CPU Upgradability:	Upgradable
Processor Main Features:	Intel Turbo Boost Technology
Chipset Type:	Intel C262

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	8 - 90% RH (non-condensing)

Dimensions & Weight

Width:	37.7 cm
Depth:	46.7 cm
Height:	25.54 cm
Weight:	7.97 kg

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 1 year - on-site
--------------------	--

Operating System / Software

OS Certified:	SUSE Linux Enterprise Server, Microsoft Windows Server, Red Hat Enterprise Linux, Oracle Solaris
---------------	--

Cache Memory

Installed Size:	6 MB
Cache Per Processor:	6 MB

RAM

Installed Size:	16 GB (installed) / 512 GB (max)
Technology:	DDR4 SDRAM - Advanced ECC
Effective Memory Speed:	2400 MHz
Rated Memory Speed:	2200 MHz
Form Factor:	DIMM 288-pin
Slots:	16 (Total) / 15 (empty)
Features:	HP SmartMemory, unbuffered
Configuration Features:	1 x 16 GB
RAM Supported:	512 GB registered - Advanced ECC ; Load-Reduced - Advanced ECC

Hard Drive

Type:	HDD
Capacity:	1 x 1 TB
Interface Type:	SATA 6Gb/s

Storage Controller

Type:	SATA
RAID Level:	RAID 0, RAID 1, RAID 5, RAID 10

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Graphics Controller

Video Interfaces:	VGA, DisplayPort
-------------------	------------------

Power

Device Type:	Power supply
Voltage Required:	AC 100-240 V (50/60 Hz)
Power Provided:	180 Watt

Miscellaneous

Theft/Intrusion Protection:	Security lock slot (cable lock sold separately)
Security Slot Type:	Kensington security slot
Compliant Standards:	ACPI, FCC Class B certified, EN 61000-3-2, ICES-003, EN 61000-3-3, EN55024, CISPR 22, FCC CFR47 Part 15, WEEE, GB 9254, CNS 13438

Expansion / Connectivity

Bays:	4 (total) / 3 (free) x internal 3.5" LFF
Slots:	1 (total) / 1 (free) x PCIe 5.0 x16 - low-profile ; 1 (total) / 1 (free) x PCIe 4.0 x8 - low-profile (x4 mode)
Interfaces:	1 x VGA ; 1 x DisplayPort 1.1a ; 4 x USB 3.2 Gen 1 - Type A (4 rear) ; 2 x USB 3.2 Gen 2 (2 in front) ; 4 x LAN (Gigabit Ethernet)

Networking

Ethernet Ports:	4 x Gigabit Ethernet
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Controller:	Integrated Lights-Out 6
Features:	Wake on LAN (WoL), ACPI support, PXE support