

HPE StoreEasy 1460 - NAS server - 8 TB



30-07-2024

SKU	R7G16A
Product Description:	HPE StoreEasy 1460 - NAS server - 8 TB
Device Type:	NAS server
Host Connectivity:	Gigabit Ethernet
Enclosure Type:	Rack-mountable - 1U
Total Storage Capacity:	8 TB
Max Supported Capacity:	32 TB
Installed Devices / Modules Qty:	4 (installed) / 4 (max)

General

Device Type:	NAS server
Host Connectivity:	Gigabit Ethernet
Enclosure Type:	Rack-mountable - 1U
Total Storage Capacity:	8 TB
Max Supported Capacity:	32 TB
Installed Devices / Modules Qty:	4 (installed) / 4 (max)
Width:	44.54 cm
Depth:	73.02 cm
Height:	8.73 cm
Weight:	16.78 kg ()

Processor / Memory

Processors Installed:	1 x Intel Xeon Bronze 3204 1.9 GHz
Number of Cores:	6-core
Max Supported Qty:	2
RAM:	16 GB DDR4
Features:	Registered

Storage Controller

Type:	RAID
Interface Type:	SATA 6Gb/s / SAS 12Gb/s

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 3 years - on-site - response time: next business day
--------------------	--

Software / System Requirements

Storage Operating System:	Microsoft Windows Storage Server IoT 2019 Standard
Software Included:	HPE iLO Advanced Premium Security Edition with 1 Year Support, HPE StoreEasy Management Console

Power

Power Device:	Internal power supply
Installed Qty:	1
Max Supported Qty:	2
Power Redundancy:	Optional
Power Redundancy Scheme:	1+1 (with optional power supply)
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Provided:	500 Watt
80 PLUS Certification:	80 PLUS Platinum

Produktdatablad genereret d. 22-07-2024 09:03.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

Storage Controller

RAID Level: RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, RAID 50, RAID 60, RAID 1 ADM, RAID 10 ADM

Hard Drive

Type: HDD - hot-swap - 3.5" LFF
Capacity: 4 x 2 TB
Interface Type: SATA 6Gb/s
Data Transfer Rate: 600 MBps
Spindle Speed: 7200 rpm
Features: Midline

Networking

Data Link Protocol: 10Mb LAN, 100Mb LAN, 1GbE

Network Services Compatibility: DNS, DHCP, Microsoft CIFS, Network File System (NFS), FTP, FTPS, Server Message Block (SMB), HTTP, HTTPS, Web-based Distributed Authoring and Versioning (WebDAV)

Miscellaneous

Compliant Standards: WEEE 2002/95/EC

Included Accessories: Rack mounting kit, lockable security bezel, 5 x hot-plug redundant fans

Expansion / Connectivity

Expansion Bays: 4 (total) / 0 (free) x hot-swap - 3.5" LFF

Expansion Slots: 1 (total) / 0 (free) x FlexibleLOM ; 1 (total) / 1 (free) x PCI Express 3.0 x8 (half-length, full-height) ; 1 (total) / 1 (free) x PCI Express 2.0 x8 (low-profile)

Interfaces: 4 x Ethernet 1000Base-T - RJ-45 ; 1 x management - RJ-45 ; 1 x serial ; VGA

