

Honeywell CK65 - data collection terminal - Android 8.1 (Oreo)

- 32 GB - 4"



In Stock(2)

SKU	CK65-LON-CSN110E
Product Description:	Honeywell CK65 - data collection terminal - Android 8.1 (Oreo) - 32 GB - 4"
Product Type:	Data collection terminal - rugged
Operating System:	Android 8.1 (Oreo)
Display:	4" colour - 480 x 800 - Multi-Touch
Processor:	Qualcomm Snapdragon (8-core)
Processor Clock Speed:	2.2 GHz
Storage:	32 GB

General

Product Type:	Data collection terminal - rugged
Operating System:	Android 8.1 (Oreo)

Display

Type:	4" colour
Resolution:	480 x 800
Touchscreen:	Multi-Touch
Features:	Outdoor viewable, glove touch mode, backlit, optical bonding, capacitive touch screen

Processor

Processor:	Qualcomm Snapdragon
Processor Clock Speed:	2.2 GHz
Number of Cores:	8-core

Memory

Storage:	32 GB
RAM:	2 GB - DDR4 SDRAM
Supported Flash Memory Cards:	microSD, microSDHC, microSDXC
Max Supported Capacity:	512 GB
Compatibility:	microSDIO

Environmental Parameters

Min Operating Temperature:	-20 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	0 - 95% (non-condensing)
Min Storage Temperature:	-30 °C
Max Storage Temperature:	70 °C

Manufacturer Warranty

Service & Support:	Limited warranty - 1 year
--------------------	---------------------------

Dimensions & Weight

Width:	8.3 cm
Depth:	4.2 cm
Height:	22.7 cm
Weight:	498 g

Miscellaneous

Sensors:	Accelerometer, ambient light sensor, gyro sensor, hall sensor
----------	---

Communications

Wireless Connectivity: 802.11a/b/g/n/ac, NFC, Bluetooth 5.0

Security Protocols & Features: LEAP, WEP, TLS, WPA, WPA2, IPsec, TTLS, PEAP, CCXv4, OPEN, PWD

Bluetooth Profiles: Hands-Free Profile (HFP), Object Push Profile (OPP), Serial Port Profile (SPP), Advanced Audio Distribution Profile (A2DP), Audio/Video Remote Control Profile (AVRCP), Phonebook Access Profile (PBAP), Generic Attribute Profile (GATT)

Multimedia

Audio: Microphone, speaker

Miscellaneous

Features: Moisture resistant, drop-resistant, push-to-talk speaker, 2x2 MiMo function, Voice over Internet Protocol (VoIP), N6703SR Standard Range Imager

Compliant Standards: FCC, MIL-STD 810G, IP64, IEC 60068-2-32

Battery

Technology: Lithium Ion

Capacity: 7000 mAh

Run Time: Up to 28 hours

Expansion and Connectivity

Expansion Slots: 1 x microSD

Interfaces: 1 x dock

Barcodes

Barcode Reader: Yes

Scan Element Type: 2D imager

Input Device

Type: Keypad

Keys Qty: 38

