

Honeywell PM43 - label printer - B/W - thermal transfer



Not in stock

SKU	PM43A14000000201
Product Description:	Honeywell PM43 - label printer - B/W - thermal transfer
Printer Type:	Label printer - thermal transfer - B/W
Weight:	15.82 kg
Localisation:	United States
Max Media Size:	Roll (11.4 cm)
Min Media Size (Custom):	19.1 mm
Max Media Size (Custom):	114.3 mm

General

Printer Type:	Label printer - thermal transfer - monochrome
Localisation:	United States

Printer

Print Speed: Up to 300 mm/sec - max speed - 203 dpi

Built-in Devices:	Touch screen
-------------------	--------------

Connectivity Technology:	Wireless
--------------------------	----------

Interface:	USB 2.0, LAN, serial, Bluetooth, Wi-Fi
------------	--

Max Resolution (B&W):	203 dpi
-----------------------	---------

Language Simulation:	ZPL, Intermec Printer Language (IPL), Intermec Fingerprint, Intermec Direct Protocol, DSIm (Datamax Interpreter), ZSim, Extensible Mark-up Language (XML), DPL
----------------------	--

Barcodes:	EAN/JAN, Code 93, Matrix 2 of 5, Industrial 2 of 5, Code 39, UCC/EAN-128, Code 49, ISBT 128, GS1 DataBar, QR code, MaxiCode, Aztec code, HIBCC, LOGMARS, MicroPDF417, Codabar, Code 128, Code 11, Code 16K, UPC, Interleaved 2 of 5, Postnet, PDF417, MSI-Plessey, Data Matrix, PLANET, Plessey, AIAG, Standard 2 of 5, Grid Matrix Code
-----------	--

Printer Features:	RFID ready, USB host
-------------------	----------------------

Dimensions & Weight

Width:	28.42 cm
Depth:	48.354 cm
Height:	29.461 cm
Weight:	15.82 kg

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)

Environmental Standards

ENERGY STAR:	Yes
--------------	-----

Software / System Requirements

Software Included:	Drivers & Utilities
OS Required:	Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits)

RAM

RAM Installed (Max):	128 MB
Technology / Form Factor:	SDRAM

Flash Memory

Flash Memory:	128 MB
---------------	--------

Power

Power Device:	Power supply - internal
Frequency Required:	50/60 Hz
Power Consumption Operational:	300 Watt

Miscellaneous

Included Accessories:	Fixed media hanger
Compliant Standards:	FCC Class A certified, UL, C-Tick, cUL, EN55022 Class A, CCC, RoHS

Expansion / Connectivity

Expansion Slots:	1 x expansion slot
Connections:	1 x LAN - RJ-45 1 x RS-232 - 9 pin D-Sub (DB-9) 1 x USB 2.0 - 4 pin USB Type B 1 x USB 2.0 - 4 pin USB Type A

Networking

Networking:	Print server
Remote Management Protocol:	SNMP 1, SNMP 3, SNMP 2c, HTTP
Security Protocols & Features:	LEAP, WEP, TLS, WPA, WPA2, AES-CCMP, TTLS, PEAP, EAP-FAST

Media Handling

Media Type:	Labels, linerless labels, fanfold paper, tag stock, tickets
Max Media Size:	Roll (11.4 cm)
Min Media Size (Custom):	19.1 mm
Max Media Size (Custom):	114.3 mm
Media Sizes:	Roll (1.9 - 11.4 cm)
Max Printing Width:	106 mm
Media Weight:	57.6 g/m² - 250 g/m²



Media Handling

Roll Maximum Outer Diameter:	213 mm
---------------------------------	--------

Roll Core Diameter:	76.2 mm, 38.1 mm
------------------------	------------------

Media Feeders:	1 x manual - 1 roll - Roll (11.4 cm)
----------------	--------------------------------------

