

Honeywell Voyager 1250g - barcode scanner



In Stock(10)

SKU	1250G-2USB
Product Description:	Honeywell Voyager 1250g - barcode scanner
Type:	Barcode scanner - handheld - USB - decoded
Colour:	Black
Minimum Bar Width:	4 mil
Scan Field Width:	44.7 cm
Scan Element Type:	Linear imager
Scan Speed:	100 line / sec

General

Type:	Barcode scanner - handheld
Colour:	Black

Barcode

Interface Type:	USB
Minimum Bar Width:	4 mil
Scan Field Width:	44.7 cm
Scan Element Type:	Linear imager
Scan Mode:	Single-pass
Scan Speed:	100 line / sec
Max Working Distance:	58.4 cm
Skew (Degrees):	60
Pitch (Degrees):	60
Print Contrast Signal (PCS):	20%

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	0 - 95% (non-condensing)
Drop Specification:	1.5 m to concrete

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years
--------------------	----------------------------

Dimensions & Weight

Width:	16.8 cm
Depth:	6 cm
Height:	7.4 cm
Weight:	133 g

Software

Software Included:	MasterMind
--------------------	------------

Power

Electric Current Required:	140 mA (operating), 85 mA (standby)
----------------------------	-------------------------------------

Miscellaneous

Cables Included:	1 x USB cable - external - 3 m
------------------	--------------------------------

Barcode

Decode
Capability:

Code 93, Matrix 2 of 5, Industrial 2 of 5,
Code 39, ISBT 128, ISBN, GS1 DataBar,
Telepen, Code 32, Code 39 Full ASCII,
EAN/JAN-8, EAN/JAN-13, UPC-A, Codabar,
Code 128, Code 11, Interleaved 2 of 5, MSI-
Plessey, China Post, UPC-E0, Trioptic
Code, UPC-A/EAN-13 with Extended
Coupon Code, ISSN, Hong Kong 2 of 5

TTL
Decoding:

Decoded

Connectivity
Technology:

Wired

OK
Notification:

Beeper, LED indicator

Features:

CodeGate, ESD (electrostatic discharge)
safe

Miscellaneous

Compliant
Standards:

FCC Class B certified, EN 61000-3-2, NOM,
EN 61000-3-3, EN55024, EN55022 Class B,
ICES-003 Class B, FCC Part 15 B, EMC,
AS/NZS 3548, RoHS, FCC CFR21 Part 1040,
IEC 60950-1, EN 60950-1, UL 60950-1
Second Edition, CSA C22.2 No. 60950-1-07,
KCC, WEEE, BSMI CNS 13438, IEC 60825-1,
cULus, GOST-R, BSMI CNS 14336, EN
60825-1

Expansion / Connectivity

Interfaces:

1 x USB - Type A

