

HP 724pn - Series 7 Pro - LED monitor - 24"



In Stock(68)

SKU	8X534A5#ABB
Product Description:	HP 724pn - Series 7 Pro - LED monitor - 24"
Device Type:	LED-backlit LCD monitor - 24"
Energy Class:	Class E
Features:	USB 3.2 Gen 1 hub
Panel Type:	IPS
Aspect Ratio:	16:10
Native Resolution:	WUXGA 1920 x 1200 at 100 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class E
Diagonal Size:	24"
Built-in Devices:	USB 3.2 Gen 1 hub
Panel Type:	IPS
Aspect Ratio:	16:10
Native Resolution:	WUXGA 1920 x 1200 at 100 Hz
Pixel Pitch:	0.27 mm
Pixel Per Inch:	94
Brightness:	350 cd/m ²
Contrast Ratio:	1500:1 / 10000000:1 (dynamic)
Colour Support:	16.7 million colours
Colour Gamut:	99% sRGB, 100% BT.709, 85% DisplayP3
Response Time:	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate:	50 - 100 Hz

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% RH (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight (Shipping)

Shipping Weight:	7.4 kg
------------------	--------

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 53.17 cm - depth: 19.5 cm - height: 52.14 cm - weight: 4.8 kg
	Without stand - width: 53.17 cm - depth: 3.85 cm - height: 34.29 cm

Software / System Requirements

Included Software:	HP Display Center, HP Display Manager
--------------------	---------------------------------------

Power

General

Horizontal Refresh Rate:	30 - 146 kHz
Horizontal Viewing Angle:	178
Vertical Viewing Angle:	178
Screen Coating:	Anti-glare, 3H Hard Coating, Haze 25%
Backlight Technology:	Edge-lit LED
Features:	4-sided micro-edge, HP Eye Ease, Flicker Free technology, Low Blue Light technology, 8-bit(6-bit + FRC) Colour Depth
Colour:	Black, silver
Dimensions (WxDxH):	53.17 cm x 19.5 cm x 52.14 cm - with stand
Weight:	4.8 kg

Connectivity

Interfaces: DisplayPort (HDCP) ; DisplayPort output (HDCP) ; HDMI (HDCP) ; USB-B upstream ; 4 x USB 3.2 Gen 1 downstream (1 charging)

Mechanical

Display Position Adjustments:	Height, tilt, swivel, pivot (rotation)
Tilt Angle:	-5/+20
Swivel Angle:	90
Rotation Angle:	180
Height Adjustment:	150 mm
VESA Mounting Interface:	100 x 100 mm

Power

Input Voltage: AC 100-240 V (50/60 Hz)

Power Consumption SDR (On mode): 19 kWh/1000h

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), detachable stand, VESA interface support, PVC free

Included Accessories: Mount adapter

Cables Included: 1 x USB-A to USB-B cable

Backlight Life: 30,000 hours

Compliant Standards: Australian-New Zealand MEPS, BIS, BSMI, CB, CCC, CECP, CEL, cTUVus, EAC, FCC, GS, ISO 9241-307, KC, NOM, KCC, PSB, SEPA, TUV S, VCCI, Vietnam MEPS, WEEE, ISC, TUV low blue light, UAE, Ukraine EE, Ukraine CoC, Ukraine DOC, WHQL, low halogen, TCO Certified Edge

Localisation: English / Europe

Security Slot Type: Kensington security slot