

HP 724pu - Series 7 Pro - LED monitor - 24"



In Stock(35)

SKU	8Y2F7A5#ABB
Product Description:	HP 724pu - Series 7 Pro - LED monitor - 24"
Device Type:	LED-backlit LCD monitor - 24"
Energy Class:	Class E
Features:	USB 3.2 Gen 1 hub, USB PD 100 Watt
Panel Type:	IPS
Aspect Ratio:	16:10
Native Resolution:	WUXGA 1920 x 1200 at 100 Hz

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class E
Diagonal Size:	24"
Built-in Devices:	USB 3.2 Gen 1 hub
USB Power Delivery:	100 Watt
Panel Type:	IPS
Aspect Ratio:	16:10
Native Resolution:	WUXGA 1920 x 1200 at 100 Hz
Pixel Pitch:	0.27 mm
Pixel Per Inch:	94
Brightness:	350 cd/m ²
Contrast Ratio:	1500:1 / 10000000:1 (dynamic)
Colour Support:	16.7 million colours
Colour Gamut:	99% sRGB, 100% BT.709, 85% DisplayP3
Response Time:	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate:	50 - 100 Hz

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% RH (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight (Shipping)

Shipping Weight:	7.8 kg
------------------	--------

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 53.17 cm - depth: 19.5 cm - height: 52.14 cm - weight: 5.2 kg
	Without stand - width: 53.17 cm - depth: 3.85 cm - height: 34.29 cm

Software / System Requirements

Included Software:	HP Display Center, HP Display Manager
--------------------	---------------------------------------

Power

Produktdatablad genereret d. 18-10-2024 10:34.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

Horizontal Refresh Rate: 30 - 75 kHz

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, Haze 25%, 3H Hard Coating

Backlight Technology: Edge-lit LED

Features: 4-sided micro-edge, HP Eye Ease, picture in picture, picture by picture, 8-bit(6-bit + FRC) Colour Depth, Flicker Free technology, Low Blue Light technology, In-Band MAC Address Pass Through (MAPT), In-Band Wake on LAN (WoL), PXE Boot

Colour: Black, silver

Dimensions (WxDxH): 53.17 cm x 19.5 cm x 52.14 cm - with stand

Weight: 5.2 kg

Connectivity

Interfaces: DisplayPort (HDCP) ; DisplayPort output (HDCP) ; HDMI (HDCP) ; USB-C/DisplayPort 1.4 Alt Mode with Power Delivery (power up to 100W) ; 4 x USB 3.2 Gen 1 downstream (2 charging) ; LAN

Power

Input Voltage: AC 100-240 V (50/60 Hz)

Power Consumption SDR (On mode): 19 kWh/1000h

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), detachable stand, VESA interface support, PVC free

Included Accessories: Mount adapter

Cables Included: 1 x USB-C to USB-C cable

Backlight Life: 30,000 hours

Compliant Standards: Australian-New Zealand MEPS, BIS, BSMI, CB, CCC, CECP, CEL, cTUVus, EAC, FCC, GS, ISO 9241-307, KC, KCC, NOM, PSB, SEPA, TUV S, VCCI, Vietnam MEPS, WEEE, ISC, TUV low blue light, UAE, Ukraine EE, WHQL, Ukraine CoC, Ukraine DOC, low halogen, TCO Certified Edge

Localisation: English / Europe

Security Slot Type: Kensington security slot

Mechanical

Display Position Adjustments: Height, tilt, swivel, pivot (rotation)

Tilt Angle: -5/+20

Swivel Angle: 90

Rotation Angle: 180

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm