

HP 727pk - Series 7 Pro - LED monitor - 4K - 27" - HDR



In Stock(7)

SKU	8J9G2A5#ABB
Product Description:	HP 727pk - Series 7 Pro - LED monitor - 4K - 27" - HDR
Device Type:	LED-backlit LCD monitor - 27"
Energy Class:	Class F
Daisy Chaining:	Yes
Features:	USB 3.2 Gen 2 hub, KVM Switch, USB PD 100 Watt
Panel Type:	IPS Black
Aspect Ratio:	16:9

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class F
Energy Class (HDR):	Class G
Diagonal Size:	27"
Daisy Chaining:	Yes
Built-in Devices:	USB 3.2 Gen 2 hub, KVM Switch
USB Power Delivery:	100 Watt
Panel Type:	IPS Black
Aspect Ratio:	16:9
Native Resolution:	4K 3840 x 2160 at 60 Hz
Pixel Pitch:	0.15 mm
Pixel Per Inch:	163
Brightness:	400 cd/m ²
Contrast Ratio:	2000:1
HDR Format:	HDR400

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% RH (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight (Shipping)

Shipping Width:	71.5 cm
Shipping Depth:	16.1 cm
Shipping Height:	45.5 cm
Shipping Weight:	9.8 kg

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 61.34 cm - depth: 22.52 cm - height: 54.05 cm - weight: 6.5 kg Without stand - width: 61.34 cm - depth: 7.45 cm - height: 35.4 cm
------------------------------	---

Software / System Requirements

Produktdatablad genereret d. 19-09-2024 03:51.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

HDR Certification:	DisplayHDR 400
Colour Support:	1.07 billion colours
Colour Gamut:	100% sRGB, 98% DisplayP3
Response Time:	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate:	29 - 60 Hz
Horizontal Refresh Rate:	30 - 140 kHz
Horizontal Viewing Angle:	178
Vertical Viewing Angle:	178
Screen Coating:	Anti-glare, Haze 25%, 3H Hard Coating
Backlight Technology:	Edge-lit LED
Features:	4-sided micro-edge, Flicker Free technology, Low Blue Light technology, HP Eye Ease, 10-bit(8-bit + FRC) Colour Depth, VESA DisplayHDR 400, Color Calibrated, Pantone calibrated, Out-of-Band MAC Address Pass Through (MAPT), Out-of-Band Wake on LAN (WoL), Picture-in-Picture, ambient light sensor, picture by picture
Colour:	Black, silver
Dimensions (WxDxH):	61.34 cm x 22.52 cm x 54.05 cm - with stand
Weight:	6.5 kg

Connectivity

Interfaces:	DisplayPort (HDCP) ; DisplayPort output (HDCP) ; HDMI (HDCP) ; 5 x USB 3.2 Gen 2 (1 charging) ; Thunderbolt 4/USB4/DisplayPort 1.4 (DisplayPort Alt Mode, data, power up to 100W) ; Network (RJ-45) ; Thunderbolt 4 (charging)
-------------	--

Software / System Requirements

Included Software:	HP Display Center, HP Display Manager
--------------------	---------------------------------------

Power

Input Voltage:	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode):	26 kWh/1000h
Power Consumption HDR (On mode):	46 kWh/1000h
Power Consumption (Typical):	43 Watt
Power Consumption (Max):	215 Watt
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Features:	Security lock slot (cable lock sold separately), detachable stand, VESA interface support
-----------	---

Included Accessories:	VESA mount
-----------------------	------------

Cables Included:	1 x Thunderbolt cable
------------------	-----------------------

Backlight Life:	30,000 hours
-----------------	--------------

Compliant Standards:	BIS, BSMI, CB, CCC, CECP, CEL, EAC, FCC, ISO 9241-307, KCC, KC, NOM, PSB, RCM, SEPA, TUV S, UL, CSA, VCCI, WEEE, ISC, low halogen, TCO Certified Edge, ICE, UAE, GS, Ukraine EE, Belarus Energy, Korea MEPS, CEL Grade 2
----------------------	--

Localisation:	English / Europe
---------------	------------------

Mechanical

Display Position Adjustments: Height, tilt, swivel, pivot (rotation)

Tilt Angle: -5/+20

Swivel Angle: 90

Rotation Angle: 180

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

