

HP 732pk - Series 7 Pro - LED monitor - 4K - 32" - HDR



In Stock(22)

SKU	8Y2K9A5#ABB
Product Description:	HP 732pk - Series 7 Pro - LED monitor - 4K - 32" - HDR
Device Type:	LED-backlit LCD monitor - 32"
Features:	USB 3.2 Gen 1 hub, KVM Switch, USB PD 100 Watt
Panel Type:	IPS Black
Aspect Ratio:	16:9
Native Resolution:	4K 3840 x 2160 at 60 Hz
Pixel Pitch:	0.18 mm

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Diagonal Size:	32"
Viewable Size:	31.5"
Built-in Devices:	USB 3.2 Gen 1 hub, KVM Switch
USB Power Delivery:	100 Watt
Panel Type:	IPS Black
Aspect Ratio:	16:9
Native Resolution:	4K 3840 x 2160 at 60 Hz
Pixel Pitch:	0.18 mm
Pixel Per Inch:	140
Brightness:	400 cd/m ²
Contrast Ratio:	2000:1 / 10000000:1 (dynamic)
HDR Format:	HDR400
Colour Support:	1.07 billion colours
Colour Gamut:	100% sRGB, 98% DisplayP3

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% RH (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight (Shipping)

Shipping Width:	81.6 cm
Shipping Depth:	18.5 cm
Shipping Height:	50.4 cm
Shipping Weight:	13.7 kg

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 71.35 cm - depth: 21.7 cm - height: 60.49 cm - weight: 8.77 kg Without stand - width: 71.35 cm - depth: 4.7 cm - height: 41.59 cm
------------------------------	---

General

Response Time: 5 ms (grey-to-grey with overdrive)

Vertical Refresh Rate: 29 - 60 Hz

Horizontal Refresh Rate: 30 - 135 kHz

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, Haze 25%, 3H Hard Coating

Backlight Technology: Edge-lit LED

Features: 4-sided micro-edge, Flicker Free technology, Low Blue Light technology, HP Eye Ease, 10-bit(8-bit + FRC) Colour Depth, VESA DisplayHDR 400, Color Calibrated, Out-of-Band MAC Address Pass Through (MAPT), Out-of-Band Wake on LAN (WoL), PXE Boot, Picture-in-Picture, Picture-by-Picture

Colour: Black, silver

Dimensions (WxDxH): 71.35 cm x 21.7 cm x 60.49 cm - with stand

Weight: 8.77 kg

Connectivity

Interfaces: DisplayPort (HDCP) ; DisplayPort output (HDCP) ; HDMI (HDCP) ; USB 3.2 Gen 1 upstream (Type B) ; 4 x USB 3.2 Gen 1 downstream ; Thunderbolt 4/USB-C 3.2 Gen 2 upstream/DisplayPort 1.4 (DisplayPort Alt Mode, data, power up to 100W) ; Network (RJ-45)

Mechanical

Display Position Adjustments: Height, tilt, swivel, pivot (rotation)

Tilt Angle: -5/+20

Software / System Requirements

Included Software: HP Display Center, HP Display Manager

Power

Input Voltage: AC 100-240 V (50/60 Hz)

Power Consumption (Typical): 48 Watt

Power Consumption (Max): 205 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), detachable stand, VESA interface support

Cables Included: 1 x USB type A to USB type B cable ; 1 x Thunderbolt cable

Backlight Life: 30,000 hours

Compliant Standards: MEPS, CB, CEL, China CCC, China CECP, C-Tick, KCC, Korea MEPS, Mexico NOM, PSB, RCM, SEPA, S Mark, BSMI, VCCI, Vietnam MEPS, EuP Lot 26, CEC, South Africa Energy Label, Mexico Energy label, UAE, TUV GS, NRCS, Belarus Energy, BIS, ISC, Ukraine EE, Ukraine CoC, Ukraine DOC, WHQL, low halogen

Localisation: English / Europe

Security Slot Type: Kensington security slot

Mechanical

Swivel Angle: 90

Rotation Angle: -90/+90

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

