

HP 738pu - Series 7 Pro - LED monitor - curved - 38" - HDR



In Stock(26)

SKU	8K167A5#ABB
Product Description:	HP 738pu - Series 7 Pro - LED monitor - curved - 38" - HDR
Device Type:	LED-backlit LCD monitor - 38"
Energy Class:	Class G
Curved Screen:	Yes
Daisy Chaining:	Yes
Features:	USB 3.2 Gen 1 hub, USB PD 100 Watt
Panel Type:	IPS Black

General

Display Type:	LED-backlit LCD monitor / TFT active matrix
Energy Class:	Class G
Energy Class (HDR):	Class G
Diagonal Size:	38"
Viewable Size:	37.52"
Curved Screen:	Yes (2300R)
Daisy Chaining:	Yes
Built-in Devices:	USB 3.2 Gen 1 hub
USB Power Delivery:	100 Watt
Panel Type:	IPS Black
Aspect Ratio:	21:9
Native Resolution:	WQHD+ 3840 x 1600 at 60 Hz
Pixel Pitch:	0.23 mm
Pixel Per Inch:	111
Brightness:	400 cd/m ²
Contrast Ratio:	2000:1

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80% RH (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Sustainability Information

ENERGY STAR Certified:	Yes
------------------------	-----

Dimensions & Weight (Shipping)

Shipping Width:	106 cm
Shipping Depth:	22.6 cm
Shipping Height:	52.7 cm
Shipping Weight:	18.9 kg

Dimensions & Weight

Dimensions & Weight Details:	With stand - width: 89.44 cm - depth: 26.69 cm - height: 58.1 cm - weight: 12.25 kg Without stand - width: 89.44 cm - depth: 10.84 cm - height: 39.69 cm
------------------------------	--

Software / System Requirements

Produktdatablad genereret d. 19-09-2024 03:38.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

HDR Format: HDR400

HDR Certification: DisplayHDR 400

Colour Support: 1.07 billion colours

Colour Gamut: 100% sRGB, 98% DisplayP3

Response Time: 5 ms (grey-to-grey with overdrive)

Vertical Refresh Rate: 30 - 60 Hz

Horizontal Refresh Rate: 30 - 140 kHz

Horizontal Viewing Angle: 178

Vertical Viewing Angle: 178

Screen Coating: Anti-glare, Haze 25%, 3H Hard Coating

Backlight Technology: Edge-lit LED

Features: 3-sided borderless, Flicker Free technology, 10-bit(8-bit + FRC) Colour Depth, Low Blue Light technology, HP Eye Ease, Out-of-Band MAC Address Pass Through (MAPT), Out-of-Band Wake on LAN (WoL), PXE Boot, DTS Virtual:X, Pantone Validated, Factory Calibration

Colour: Black, silver

Dimensions (WxDxH): 89.44 cm x 26.69 cm x 58.1 cm - with stand

Weight: 12.25 kg

Audio

Type: Speakers - quadraphonic

Output Power / Channel: 3 Watt

Connectivity

Software / System Requirements

Included Software: HP Display Center, HP Display Manager

Power

Input Voltage: AC 100-240 V (50/60 Hz)

Power Consumption SDR (On mode): 38 kWh/1000h

Power Consumption HDR (On mode): 75 kWh/1000h

Power Consumption (Typical): 62 Watt

Power Consumption (Max): 318 Watt

Power Consumption Stand by: 0.5 Watt

Miscellaneous

Features: Security lock slot (cable lock sold separately), detachable stand, VESA interface support

Included Accessories: Mount adapter

Cables Included: 1 x Thunderbolt cable

Backlight Life: 30,000 hours

Compliant Standards: BIS, BSMI, CB, CCC, CECP, CEL, EAC, FCC, ISO 9241-307, KC, KCC, NOM, PSB, RCM, SEPA, TUV S, UL, CSA, VCCI, WEEE, ISC, TUV low blue light, UAE, ICE, GS, Ukraine EE, Belarus EE, Korea MEPS, CEL Grade 2, low halogen

Localisation: English / Europe

Security Slot Type: Kensington security slot

Mechanical

Display Position Adjustments: Height, tilt, swivel

Tilt Angle: -5/+20

Swivel Angle: 20

Height Adjustment: 150 mm

VESA Mounting Interface: 100 x 100 mm

Connectivity

DisplayPort (HDCP) ; DisplayPort output (HDCP) ; HDMI (HDCP) ; USB-C (DisplayPort Alt Mode, data, power up to 65W) ; Thunderbolt 4/USB-C 3.2 Gen 2 upstream/DisplayPort 1.4 (DisplayPort Alt Mode, data, power up to 100W) ; Network (RJ-45) ; Thunderbolt 4 output (daisy chain, power up to 15W) ; 4 x USB 3.2 Gen 1 downstream ; USB 3.2 Gen 1 downstream (power up to 7.5W)

